## **Technical Data**



#### Performance you can trust

### PR SPRAY

## Silicone Wet Film Mould Release Agent

PR Spray is designed to give fast, efficient clean release in critical moulding applications. It penetrates and spreads to all parts of the most intricate mould to give full, clean release, with improved gloss finish.

PR Spray gives a fine, controlled spray with complete coverage for maximum economy. Use on all types of blow, injection, flow and compression moulding, particularly on complex tooling. Helps overcome difficulties encountered during setting and start up.

#### **Features**

- Effective release of plastics and rubber moulded parts.
- Heat resistant wet film up to 200°C.
- · Gives improved gloss finish.
- Particularly suited to delicate or intricate parts.

#### **Directions for Use**

Shake well, hold upright and spray from a distance of approximately 15-30cm (6-12 inches). One pass usually provides sufficient coating. Ensure adequate ventilation. Do not spray onto naked flame or any incandescent material.

T +44 (0) 113 232 2600 F +44 (0) 113 232 2740 E customer-service@rocol.com www.rocol.com ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67 Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SLA 3BL ROCOL A division of MY Ltd









# **Technical Data**



Performance you can trust

## PR SPRAY

Propellant	Hydrocarbon blend
Solvent	Isoparaffinic Hydrocarbon
Base Fluid	Blend of silicone oils
Colour	Colourless
Temperature Range	Up to +200°C
Storage	Storage temperature should be kept below 50°C. Storage area should be out of direct sunlight.
Pack Sizes – Part Codes	400ml - 72015

Date: Jan-09

T +44 (0) 113 232 2600 F +44 (0) 113 232 2740 E customer-service@rocol.com

www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67 Registered Office: Admirál House, St Leonard's Road, Windsor, Berkshire SL/ 3BL ROCOL A division of MW Ltd









