INDIVIDUAL LOUDSPEAKERS



GENERAL DESCRIPTION

The **30C25Z45OT** is a 3" square frame loudspeaker with a 2.35 oz. ceramic magnet, 45 Ohm nominal impedance and a moisture resistant cone.

INTENDED USE - Indoor and Outdoor Environment

Program Material Installation

Signal tones, voice and music

Loudspeaker mount is a #8-32 tapped hole,

center rear of device

AUDIO SPECIFICATIONS

Frequency Response Power Handling¹ Impedances Available 300 Hz - 10kHz 4W

Cone Finish Options

45

Magnet Material

Weather-Resistant Ceramic

Weight

2.35 oz


Depth 1.190 in




MOISTURE RESISTANT

3" O.D. loudspeaker, 2.35 oz. magnet, 45Ω impedance, moisture resistant





Recommended construction sequences, installation instructions, and A&E Specifications are available in various formats in the QUAM Architects' and Engineers' Resources section on the web at: www.QuamSpeakers.com









QUAM-NICHOLS COMPANY, INC. 234 East Marquette Rd. Chicago, IL. 60637 Tel: 1-800-NEED-NOW (800-633-3669) Fax: 1-888-NEED-NOW (888-633-3669) e-mail: NeedNow@QNC.com www.QuamSpeakers.com

¹Loudspeaker Power Rating per EIA 426A