## **CADDY CAT HP J-Hook Tree, Ceiling Mount – CAT32HPDCM4**











- Ideal for attaching to concrete, steel or wood surfaces
- Provides optimal support for high-performance data cable, up to and including Cat 5e, Cat 6, Cat 6A, Cat 7 and fibre optic
- Ready to use out of the box, saving installation time and labor
- Requires no screws, rivets or special tools for assembly
- · Single- or double-sided tree configurations provide multiple J-Hooks with one structural attachment
- Provides superior fill capacity and load rating over most other non-continuous cable support alternatives
- Complies with EN 50174-2
- Meets ISO®/IEC 14763-2, TIA 568-C and TIA 569-C









| Part Number        | CAT32HPDCM4   |
|--------------------|---------------|
| Material           | Steel         |
| Finish             | Pregalvanized |
| Туре               | Double Sided  |
| Diameter (Ø)       | 2"            |
| Tiers              | 4             |
| Height (H)         | 20 1/4"       |
| Width (W)          | 5 13/16"      |
| Hole Size 1 (HS1)  | 0.405"        |
| Hole Size 2 (HS2)  | 0.185"        |
| A                  | 1 7/16"       |
| В                  | 2"            |
| Static Load 1 (F1) | 480 lb        |
| Static Load 2 (F2) | 180 lb        |
| Certifications     | cULus         |





| Part Number                 | CAT32HPDCM4   |
|-----------------------------|---------------|
| Standard Packaging Quantity | 5 рс          |
| UPC                         | 78285679931   |
| EAN-13                      | 8711893138214 |

Static loads represent maximum load limit of J-Hook tree. Static load limit of each J-Hook is 60 lb (270 N). Refer to Static Load 1 when fastening J-Hook tree using Hole Size 1. Refer to Static Load 2 when fastening J-Hook tree using Hole Size 2. Non-continuous supports may not exceed spacing of 5' (1.5 m) per TIA 569-C.9.7 and EN 50174-2.

ISO is a registered trademark of International Organization for Standardization. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

## WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2016 Pentair All rights reserved Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates. All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.



