


Type TXL SAE J1128 Extra Thin Wall



Applications

For general circuit wiring where resistance to oxidation at higher temperatures is necessary. Use where heat and flame resistance is a stringent requirement, such as in the engine compartment of vehicles.

Specifications

CONDUCTOR: Bare copper

INSULATION: Cross-linked Polyethylene (XLP)

- STANDARDS: SAE J1128

TEMPERATURE: -40°C to 125°C

NOMINAL VOLTAGE: 60 V DC (25 V AC) or less

1. For use in automotive applications where reduced diameter and weight is required. 2. Available on reels or in a drumpack. 3. Striped and solid colors available with custom printing and/or numbering. 4. Available cut and stripped to length, ready for termination. 5. Tinned copper conductors available, special order.

Part No.	SAE Wire Size mm²	Conductor AWG	No. of Strands	Wall Thickness Min. (mm)	Wall Thickness Min. (in.)	Nom. O.D. (mm)	Nom. O.D. (in.)	Approx. Wt. lb./1,000 ft.
6TXL-2201-XX	0.35	22	7x30	0.4064	0.016	1.575	0.062	3.8
6TXL-2001-XX	0.5	20	7x28	0.4064	0.016	1.778	0.070	5.1
6TXL-1801-XX	0.8	18	19x30*	0.4064	0.016	1.981	0.078	6.9
6TXL-1601-XX	1	16	19x29	0.4064	0.016	2.261	0.089	9.2
6TXL-1401-XX	2	14	19x27	0.4064	0.016	2.591	0.102	14.4
6TXL-1201-XX	3	12	19x25	0.4572	0.018	3.251	0.127	22.8
6TXL-1001-XX	5	10	19x23	0.508	0.020	3.937	0.155	34.8
6TXL-0801-XX	8	8	19x0.0295	0.5588	0.020	4.851	0.191	52.1

Electrical and Electronic Wire & Cable • Enterprise Cabling & Security Solutions • Fasteners

Anixter Inc. World Headquarters • 2301 Patriot Boulevard, Glenview, IL 60026-8020 • 1.800.ANIXTER • 224.521.8000 • anixter.com

Anixter is a leading global supplier of communications and security products, electrical and electronic wire and cable, fasteners and other small components. We help our customers specify solutions and make informed purchasing decisions around technology, applications and relevant standards. Throughout the world, we provide innovative supply chain management solutions to reduce our customers' total cost of production and implementation.

^{*} Alternate construction 19x31. All part numbers require color code designation.

Product Data Sheet | Anixter Catalog Page



Automotive Circuit Size Primary Wire Color Code

Number	Color	Letter	Color	Examples
1	Brown	M	Maroon	For white with black stripe – 90
2	Red	Р	Pink	For green with yellow stripe - 54
3	Orange	S	Silver	For white with a black and red stripe - 902
4	Yellow	T	Tan	
5	Green			
6	Blue	D	Dark	For white and black twisted conductor 9/0
7	Violet/Purple	L	Light	For white, black, and red twisted conductors 9/0/2
8	Gray			
9	White			(D6=Dark Blue)

Bectrical and Bectronic Wire & Cable • Enterprise Cabling & Security Solutions • Fasteners

Anixter Inc. World Headquarters • 2301 Patriot Boulevard, Glenview, IL 60026-8020 • 1.800.ANIXTER • 224.521.8000 • anixter.com