

VGA Video/Audio Extender via CAT5

XTENDEX®

Extend a VGA monitor up to 600 feet away from a computer

- Ideal solution for digital signage applications.
- Supports local and remote VGA monitors.
- Supports resolutions to 1920x1440.
- Available with optional stereo audio or RS232 control.
- Built-in surge protection.
- Sharpest and clearest VGA quality over CAT5 of any manufacturer.
- Optional 2-port local unit available – extend two remote units up to 600 feet. (183 meters)
 - Local VGA monitor not available on 2-port local units.
- Use in-house CAT5/5e/6/6a phone wiring to locate a monitor remotely.
- Optional VESA mounting bracket is available for mounting the remote unit to the back of a flat panel monitor.



XTENDEX® ST-C5V-600 (Remote & Local Unit)

- **Audio**
- **RS232**
- **Local Unit Supporting Two Remote Monitors**

The XTENDEX® VGA Extender transmits VGA video up to 600 feet away from a computer using CAT5/5e/6/6a cable. Each video extender consists of a local unit that connects to a computer and also supplies video to a local monitor, and a remote unit that connects to a monitor.

Specifications

Local Unit

Host Connection

- Supports a PC, SUN, MAC or NTI switch with VGA video.
- Multiplatform support: Windows 2000/XP/Vista/7, Windows Server 2000/2003/2008, Solaris, Linux, FreeBSD, and MAC OS 9/10.
- Male 15-pin HD connector for computer connection.
- Optional RS232 support - female 9-pin D connector.
- Optional stereo audio support - 3.5 mm stereo plug.
- ST-2C5V-L-600: female 15-pin HD connector for downloading DDC table for remote monitor.

Local Access

- Crisp and clear 1920x1440 video resolution.
- Female 15-pin HD connector for local VGA monitor.
- Video signal to noise ratio: >55dB
- Distortion: 65dB at 5MHz
- Optional RS232 support - male 9-pin D connector.
- Optional stereo audio support - 3.5 mm stereo jack.
- Local VGA monitor not available on 2-port local units, ST-2C5V-L-600.

Environment

- Operating temperature: 32 to 100°F (0 to 38°C).
- Storage temperature: -20 to 140°F (-30 to 60°C).
- Operating and Storage Relative Humidity: 17 - 90% non-condensing RH.

Cables

- Use CAT5, CAT5e or CAT6 solid straight through cable for TIA/EIA-568B wiring terminated with standard RJ45 connectors (not included).

Regulatory Approvals

- CE, RoHS
- TAA compliant

Remote Unit

- Supports resolutions up to 1920x1440; refer to the resolution chart below for resolutions at different lengths.
- Video signal to noise ratio: >55dB
- Distortion: 65dB at 5MHz
- Female 15-pin HD connector.
- Optional 3.5 mm stereo audio connection.
- Optional male 9-pin D connector for RS232.

Video Quality Adjustment

- Video quality adjustment for different lengths of CAT5/5e/6/6a cable is done manually for the video-only extender, and automatically for audio/video or video/RS232 extender.

Power

- Local and remote unit: 110 to 220 VAC at 50 or 60 Hz via AC adapter. (Country-specific AC adapters included.)
- Power Consumption: 10 W (each - local and remote unit).
- Use the PWR-48V-9V0-6A or PWR-12V-9V0-6A DC-DC power converter to install the local unit in a Telecom environment.

MTBF

| NTI Part # | MTBF (hrs) | NTI Part # | MTBF (hrs) |
|----------------------|------------|-----------------------|------------|
| ST-C5V-600 (local) | 88,708 | ST-C5V-600 (remote) | 80,625 |
| ST-C5VA-600 (local) | 84,744 | ST-C5VA-600 (remote) | 82,214 |
| ST-C5VRS-600 (local) | 82,338 | ST-C5VRS-600 (remote) | 79,714 |

Dimensions:

- WxDxH: 3.5x3.1x1.2 in (89x79x30 mm)
- Weight: 1.2 lbs (0.54 kg)

Warranty


- Two Years

VGA Video/Audio Extender via CAT5


XTENDEX®

Extend a VGA monitor up to 600 feet away from a computer

Configuration and Cable Illustration



Configuration and Cable Illustration of ST-2C5V-L-600 and ST-C5V-R-600



Options

Stereo Audio

- Stereo audio can be heard both locally and remotely.
- Frequency response: 20 Hz to 20 kHz, +/-1 dB.
- Signal-to-Noise Ratio (SNR): 76 dBA.
- Total Harmonic Distortion and Noise (THD+N): 0.017%.
- Stereo crosstalk: -70 dB.
- Input impedance: 10k Ohms.
- Line level output; supports multimedia speakers.
- Maximum I/O levels: 3.1Vp-p (line level).
- CD quality audio output.

RS232 Control

- Supports TXD, RXD, DTR, DSR, CTS and RTS.
- Baud rate up to 56000.
- Support for a touch screen monitor.

Local Unit Supporting Two Remote Monitors

- Two RJ45 connectors for connecting two remote units.
 - The monitors connected to each remote unit simultaneously display the same image.
- Features push button for downloading DDC data from monitor connected to VGA connector.

VESA Mounting Bracket

- Use to mount the remote unit to the back of a flat panel monitor.
- Compliant to VESA 75 and 100 mm (3 and 3.9 in) mounting hole patterns.
- Dimensions WxH (in): 9.7x4.8
- Compatible with the remote unit only.



Remote unit mounted to the back of a flat panel monitor using ST-C5MK-VESA mounting kit

Distances and Resolutions for CAT5/Cat5e and CAT6 Cables

| Cable | Distance (feet) | Maximum Resolution |
|---------------------------|-----------------|--------------------|
| CAT5/CAT5e (UTP) | 600 | 1024x768 at 60Hz |
| CAT5/CAT5e (UTP) | 400 | 1280x1024 at 60Hz |
| CAT5/CAT5e (UTP) | 300 | 1600x1200 at 60Hz |
| CAT5/CAT5e (UTP) | 100 | 1920x1440 at 60Hz |
| CAT5/5e (STP), CAT6 (UTP) | 300 | 1024x768 at 60Hz |
| CAT5/5e (STP), CAT6 (UTP) | 200 | 1280x1024 at 60Hz |
| CAT5/5e (STP), CAT6 (UTP) | 100 | 1920x1440 at 60Hz |

VGA Extender Models

| Supported Features | Local or Remote | # of Ports | NTI Part # |
|--------------------|-----------------|------------|---------------|
| VGA | Both | 1 | ST-C5V-600 |
| VGA + Audio | Both | 1 | ST-C5VA-600 |
| VGA + RS232 | Both | 1 | ST-C5VRS-600 |
| VGA | Local | 2 | ST-2C5V-L-600 |
| VGA | Remote | 1 | ST-C5V-R-600 |
| VGA + Audio | Remote | 1 | ST-C5VA-R-600 |