HellermannTyton

157-00143



Article Number: 157-00143

Cable Tie 6" with Oval Fir Tree, PA66HIRHS, Black, 5000/CTN





Base Data

Local Order Number 157-00143

Type T50SOSFTOVALU

Color Black (BK)

Features and Benefits • The fir tree branch design on all four sides makes a 360 degree interface with the panel, creating a more secure fit

• The disc on the top of the fir tree covers the hole and minimizes the ingress of water and dirt.

• The oval hole fir tree fits 4 common automotive oval hole sizes.

Product Description The one-piece cable tie and fixing offers a simple and easy to use method of bundling and fixing cables, the innovative design of the fir tree creates an interface with four different size holes that are commone in the automotive industry. The fir tree branch design on all four sides makes a 360 degree interface with the panel, creating a more

secure fit into the hole.

The 'disc' on the top of the fir tree covers the hole and minimises the ingress of water and dirt.

Short Description Cable Tie 6" with Oval Fir Tree, PA66HIRHS, Black, 5000/CTN

Product Dimensions

Minimum Tensile Strength (Imperial) 50.0 lbs

Minimum Tensile Strength (Metric) 222.0 N

Length L (Imperial) 6.0 "

Length L (Metric) 174.0 mm

Fixation Method Fir Tree for oval holes

Identification Plate Position none

Releasable Closure

Tie Closure plastic pawl

Bundle Diameter Min. (Imperial) 0.07 "

Bundle Diameter Min. (Metric) 1.8 mm

Bundle Diameter Max. (Imperial) 1.0 "

Bundle Diameter Max. (Metric) 35.0 mm

Panel Thickness Max. (Imperial) 0.2 "

Panel Thickness Max. (Metric) 6.75 mm

Panel Thickness Min. (Imperial) 0.02 "

Panel Thickness Min. (Metric) 0.6 mm

Mounting Hole Diameter D (Imperial) 0.24 x 0.48 "; 0.25 x 0.50 ", 0.25 x 0.5 "; 0.27 x 0.47 "

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 500

Material and Specifications

Material Polyamide 6.6 heat stabilized (PA66HS)

Material Shortcut PA66HS

ROHS Compliant Yes

© HellermannTyton 2015