



596-00801



Article Number: 596-00801

Hazard Label, 3" X 3", Polyester, Yellow, 50/RL

 RoHS

 Download spec sheet

Base Data

Local Order Number	596-00801
Type	HL3X3YE
Color	Yellow (YE)
Features and Benefits	<ul style="list-style-type: none">• Made with UV stable inks and materials for durability and weather resistance• Polyester is resistant to chemicals and solvents and will remain legible in dirty environments.• High abrasion and scuff resistance for high performance labeling.• Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections
Product Description	HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the National Electrical Code and the International Fire Code as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.
Short Description	Hazard Label, 3" X3", Polyester, Yellow, 50/RL

Product Dimensions

Width W (Imperial)	3.0 "
Width W (Metric)	76.2 mm
Height H (Imperial)	3.0 "
Height H (Metric)	76.2 mm

Logistics and Packaging

Quantity Per	reel
Package Quantity	50
Package Quantity (Metric)	50

Material and Specifications

Material	Polyester (PET)
Material Shortcut	PET
Adhesive Shortcut	Acrylic
Adhesive	Acrylic
Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Halogenfree	Yes
Operating Temperature	-40°F to +302°F (-40°C to +150°C)
ROHS Compliant	Yes
UL Recognized (US and Canada)	No

UL Recognized (US) Yes