

2

2

B

A

1						
	PANDUIT P/N			WEIGHT		
	GM	GM-A0268BL		3.70kg	3.70kg (8.151b)	
ES : DENT I F PART_NO).	5 M(S) <u>C(</u>	-20R, G DNITORE	AL, (10) ATEWAY-EN D, 120V / HASE PDU	IABLED	
1) QUI 4) M6 4) #12 PRIMARY ECONDA ECONDA ACTOR, CONNECT ACTOR, CONNECT ACTOR, CONNECT CONNECT CONNECT CONNECT CONNECT	2-24 × CDIMEN RY DIN POWER (FREQU TED VIA N BE A Y DMPLIAN	RT GU MOUN 1/2" SIONS ENSI AMPS ENCY SER CCESS	JIDE NTING S MOUNTI GARE I ONS IN VOLTS MONIT IAL CON	NG SCREWS N MILLIME [INCHES] , kWh, kV ORING. WH NECTION T NIT DISPL	TERS, (A, POWE IEN (O GATEW)	
'WW.PAN 'RODUCT 1AXIMUN NSTALL	NDUIT.C S APPL 1 AVAIL LATION	OM F(ICABL ABLE SHALL	DR A CU _E FOR INPUT _ COMPL	RRENT LIS USE WITH POWER = 1 Y WITH AL TE, AND L	THIS PA .9 kW .L	
w	3 METEI Inlet i					
)IMENSIONS, SIGNATUTE B THE JOB WILL SIGNED APPR	YOU CHECK I NOTES, AND DX. L NOT PROGRI DVAL. PLEASI G PROOF AS	SIGN THE ESS WITHO E DO NOT	CLIENT	E		A
SMARTZ	ONE GA	TEWA	(-ENABL	ED M SERI	ES RACK	PDU
			1-A02 Jstomer d			
AA0268AP/01.PRT ATASET FILE NAME AA0268CP_DC/01A.PRT						
MATERIAL/COLOR: INLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: NCHES NCHES XXX +/- XXX +/- XXXX +/- XXXX +/-						
THIRD ANGLE PROJECTION AAO268CP_D						
	4/30/14	MRWA	NONE	SHT	1 OF 1	B

1