

1			
	PANDUIT P/N	WEIGHT	
	GM-A0273**	13.8kg (30.4 b)	
FICATIO <u>D.</u> 73**	N: VERTICAL, MIXE (6) C19, GATEW Monitored, 208 Three-phase de <u>Color</u> Black	AY-ENABLED V / 50A /	
ICK-STA Y DIMEN ARY DIM (L1, L2 kWh, ring. w tion to t displ omplian our on- our on- our on- nduit.c ts appl M avail _Ation Able na	PONENTS: RT GUIDE SIONS ARE IN MILL ENSIONS IN IINCHE , L3) LEVEL POWER KVA, POWER FACTOR HEN CONNECTED VIA GATEWAY, DATA CA AY OR REMOTELY T LINE CATALOG AT OM FOR A CURRENT ICABLE FOR USE WI ABLE INPUT POWER SHALL COMPLY WITH TIONAL, STATE, AN CIRCUIT IDENTIFIC	S] (AMPS, , FREQUENCY) SERIAL N BE ACCESSED LIST OF TH THIS PART. = 14.4 kW ALL D LOCAL CODES.	B
10 FOOT ER CORD		82.5 [3.25]	
	SIDE VIEW		
DIMENSIONS, I DIGNATUTE BO THE JOB WILL DIGNED APPRO IN RETURNING DELIVERY.	NOT PROGRESS WITHOUT VAL. PLEASE DO NOT DELAY PROOF AS IT WILL AFFECT	Е ИТ	A
SMARTZ(ED M SERIES RACK PDU	
	GM - AO2 		
TEM REVISION NA	AA0273AP/01	DANDUIT	
Α	~~ A0273CP_DC/01A e specified, dimensional tolerances are	MATERIAL/COLOR:	-
INCHES UTHERWIS X.X +/- X.XX +/- X.XX +/- X.XXX +/-	METRIC - MILLIMETER ANGLE X. +/- X.x +/- X.x +/- +/-		
DRAWN BY DATE	THIRD ANGLE PROJECTION /26/14 MRWA 1:8	DRAWING NUMBER: AA0273CP_DC SHT 1 OF 1	
4			