

2

1						-
	PANDUIT P/N			WEIGHT		
	GMS	5-A02	85BL	X.XXkg	(XX.X b)	
IFICAT	L C P M	OCKIN 13 LC Rotec Onitc	NG, (6) NCKING A NTED), 6 NRED SWI	(ED (18) C C19 LOCKI Always on Gateway-en Tched, 23 Phase Wye	NG, (1) (BREAKER JABLED	
<u>NO.</u> 0285BL		<u>olor</u> Lack				
DARY D (L1, L KVA, PO CAN BE ELY WHI TEWAY IDUAL I ELY COMPLI, OUR OI CURREI ITH TH	TART G ENSION IMENSI 22, L3 OWER F ACCES EN CO RECEPT ANT N-LINE NT LIS IS PAR	UIDE S ARE ONS I) LEV ACTOF SED C NNECT ACLES CATA T OF T	N [INCH (EL POWE FREQU N UNIT ED VIA CAN BE CAN BE	ER (AMPS, JENCY) MON DISPLAY C SERIAL CC E SWITCHEE WWW.PANDU IS APPLICA	VOLTS, NITORING. DR DNNECTION D ON/OFF JIT.COM ABLE FOR	B
LLATIO NAL, S	N SHAL Tate,	L CON AND L	IPLY WIT .ocal co	R = 22.2 k Th all app Des Identific	PLICABLE	
		\sim			— 63.6 [2.50] -	
IO FOOT ER CORI		_	0.0 —— .54]			
SIDE VIEW VE ASK THAT YOU CHECK FULLY THE DIMENSIONS, NOTES, AND SIGN THE CLIENT DATE DATE THE JOB WILL NOT PROGRESS WITHOUT DATE PRINT PREJURNING PROOF AS IT WILL AFFECT PRINT						
SMARTZONE GATEWAY-ENABLED MS SERIES RACK PDU						
			S-A02 JSTOMER DF			
ATASET FILE NA	A0285AF ME 285CP_[SE SPECIFIED,	P/00.F DC/00A	PRT PRT DRT TOLERANCES ARE	MATERIAL/COLOR:	NDUIT	
××× +/- ×××× +/-		+/- +/-	+/-	DRAWING NUMBER:	N/A	
	$-\bigcirc$	PRO	RD ANGLE DJECTION		85CP_DC	
	/25/14	GLM	NTS	SHT 1		