

PANDUIT	P/N

WEIGHT

GM-A0929BL

## 5 kg (11 lb)

В

ら

09/10/14

JPHI

1

NOTES: 1. IDENTIFICATION: GATEWAY MONITORED ZERO-RU INLINE METER, (1) 30A NEMA L5 30P, 120V / 30A / SINGLE-PHASE PDU

PART NO. GM-A0929BL <u>COLOR</u> BLACK RAL 9005

2. ACCESSORY COMPONENTS: (4) M6 x 12mm MOUNTING SCREWS (4) M6 x 12mm MOUNTING SCREWS (4) M6 NUT (CAGED) (1) M5 NUT (NYLON INSERT) (1) M5 LOCK WASHER

3. PRIMARY DIMENSIONS ARE IN MILLIMETERS, SECONDARY DIMENSIONS IN [INCHES]

4. INPUT POWER (AMPS, VOLTS, kWh, kVA, POWER FACTOR, FREQUENCY) MONITORING. WHEN CONNECTED VIA SERIAL CONNECTION TO GATEWAY, DATA CAN BE ACCESSED VIA ON UNIT DISPLAY OR REMOTELY. 5. RoHS COMPLIANT.

6. VISIT OUR ON-LINE CATALOG AT WWW.PANDUIT.COM FOR A CURRENT LIST OF PRODUCTS APPLICABLE FOR USE WITH THIS PART.

7. MAXIMUM AVAILABLE INPUT POWER = 2.9 kW 8. INSTALLATION SHALL COMPLY WITH ALL APPLICABLE NATIONAL, STATE, AND LOCAL CODES.

WE ASK THAT YOU CHECK FULLY THE DIMENSIONS, NOTES, AND SIGNTHE CLIENT SIGNATUTE BOX. THE JOB WILL NOT PROGRESS WITHOUT SIGNED APPROVAL. PLEASE DO NOT DELAY IN RETURNING PROOF AS IT WILL AFFECT DELIVERY.		A	
SmartZone Gateway-Enabled Zero-RU Inline Meter PN: GM-A0929BL CUSTOMER DRAWING			
TTEM REVISION NAME AA0929CP/00.PRT DATASET FILE NAME AA0929CP_DS/00A.PRT	PANDUIT		
UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE:   INCHES METRIC - MILLIMETER ANGLE   X.X +/- 0.8 X.X +/- 0.8   X.XX +/- 0.018 X.XX +/- 0.46 +/- 1°   X.XX +/- 0.007 X.XX +/- 0.18 +/- 1°	MATERIAL/COLOR: BLACK RAL 9005 TEXURE FINISH		
THIRD ANGLE PROJECTION	DRAWING NUMBER: AA0929CP		

SCALE:1:5

SHEET 1 OF 1

SIZE

В