THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.



DETAIL A
(SCALE 4X)

PANDUIT P/N	WEIGHT
PN1D2A0BA12M1	10 lb (4.5 kg)

NOTES:

(1) 1. IDENTIFICATION: 1RU HORIZONTAL, (10) C13 NETWORKED & ENVRIONMENTAL MONITORED 230V / 16A / SINGLE-PHASE POU

PART NO.	COLOR
PN1D2A0BA12M1	BLACK

2. ACCESSORY COMPONENTS:
   (4) M6 x 20mm MOUNTING SCREWS
   (4) #12-24 x 1/2" MOUNTING SCREWS
3. HEXAGONS ARE FOR COMMUNICATION PURPOSES.
4. POWER (A,V,PF,KWH) MONITORING AND ENVIRONMENTAL SENSOR DATA CAN BE ACCESSED REMOTELY VIA ETHERNET CONNECTION, LOCAL DISPLAY, OR OPTIONAL REMOTE DISPLAY (PVQ-RD).
5. UNIT COMPLIES WITH IEC 60950-1, EN55022, EN55024, AND IS CE MARKED.
6. RoHS COMPLIANT.
7. VISIT OUR ON-LINE CATALOG AT WWW.PANDUIT.COM FOR A CURRENT LIST OF PRODUCTS APPLICABLE FOR USE WITH THIS PART.
8. MAXIMUM AVAILABLE INPUT POWER = 3.7 KW
9. INSTALLATION SHALL COMPLY WITH ALL APPLICABLE NATIONAL, STATE, AND LOCAL CODES.



REAR VIEW



FRONT VIEW



SIDE VIEW



PLUG
16 AMP, 250V, SINGLE-PHASE
2P/3W
IEC 60309, SPLASHPROOF

TWELVE (12)
RECEPTACLES
10 AMP, 250V
STRAIGHT BLADE
IEC 60320/C13

REV	DATE	BY	CHK	DESCRIPTION	ECN - R	CUST	SUP	OTH
01A	8-27-12	PIP	MRWA	A. REVISED DETAIL A.	09V098JC			
00A	11-22-11	MRWA	KRKE	RELEASED TO PRODUCTION	09V098JC			

MODEL FILENAME: 09V098JC/01.PRT
CAD FILENAME/LAYERS: 09V098JC_DC/01A.PRT

PANDUIT CORP TINLEY PARK, ILLINOIS

1RU HORIZONTAL, (10) C13
NETWORKED & ENVIRONMENTAL MONITORED
CUSTOMER DRAWING

UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE:
INCHES: X.X +/- 0.03; X.XX +/- 0.015; X.XXX +/- 0.005
METRIC - MILLIMETER: X. +/- 0.8; X.X +/- 0.4; X.XX +/- 0.13
ANGLE: +/- 1°

UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE GIVEN IN INCHES, THIRD ANGLE PROJECTION

DRAWN BY: MRWA
MAT'L:
SCALE: NONE
DATE: 11-22-11
CHK'D: KRKE
DRAWING NO.: 09V098JC
DWG SIZE: B