THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.



DETAIL A
(SCALE 4X)

PANDUIT P/N	WEIGHT
QZ1A1P3BN24E1	17 lb (7.7 kg)

NOTES:

1. IDENTIFICATION: VERTICAL, (24) 5-20R NETWORKED
   120V / 30A / THREE-PHASE WYE POU

PART NO.	COLOR
QZ1A1P3BN24E1	BLACK

2. ACCESSORY COMPONENTS:
   (4) #10-32 x 1/2" MOUNTING SCREWS
   (4) #12-24 x 1/2" MOUNTING SCREWS
   (2) #10-32 LOCKING COLLAR SCREWS
   (2) L-BRACKETS
3. DIMENSIONS IN PARENTHESES ARE METRIC (mm).
4. CURRENT METER - RED, 4-DIGIT LED DISPLAY PROVIDES TRUE RMS CURRENT THAT CONTINOUSLY SCROLLS THROUGH THE THREE DIFFERENT MEASURED CIRCUITS. METER DISPLAYS CIRCUIT NAME FOLLOWED BY THE MEASURED CURRENT (E.G. CR-1 REPRESENTS PHASE 1). BREAKER/PHASE (X,Y,Z) LEVEL MONITORING CAN ALSO BE ACCESSED REMOTELY VIA ETHERNET CONNECTION.
5. UL® & c-UL® LISTED 60950 AND NOM COMPLIANT.
6. RoHS COMPLIANT.
7. VISIT OUR ON-LINE CATALOG AT WWW.PANDUIT.COM FOR A CURRENT LIST OF PRODUCTS APPLICABLE FOR USE WITH THIS PART.
8. MAXIMUM AVAILABLE INPUT POWER = 8.6 KW
9. INSTALLATION SHALL COMPLY WITH ALL APPLICABLE NATIONAL, STATE, AND LOCAL CODES.







REV	DATE	BY	CHK	DESCRIPTION	ECN - R	CUST	SUP	OTH
01A	9-5-12	PIP	MRW/A	A. UPDATED NOTE #5 & 8. B. ADDED NOTE #9. C. UPDATED DETAIL A.	09V098NT			
00A	11-23-10	MAV	KRKE	RELEASED TO PRODUCTION	09V098NT			

MODEL FILENAME: 09V098NT/01.PRT
CAD FILENAME/LAYERS: 09V098NT_DC/01A.PRT

PANDUIT CORP TINLEY PARK, ILLINOIS

VERTICAL, (24) 5-20R NETWORKED
POWER OUTLET UNIT
CUSTOMER DRAWING

UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE:
INCHES: X.X +/- 0.03, X.XX +/- 0.015, X.XXX +/- 0.005
[METRIC - MILLIMETER]: X. +/- 0.8, X.X +/- 0.4, X.XX +/- 0.13
ANGLE +/- 1°
UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE GIVEN IN INCHES, THIRD ANGLE PROJECTION

DRAWN BY: MAV
MAT'L:
SCALE: NONE
DATE: 11-23-10
CHK'D: KRKE
DRAWING NO.: 09V098NT
DWG: B SIZE