


PANDUIT P/N	WEIGHT
VB1B1L2BN12J1	17 lb (7.7 kg)

9. INSTALLATION SHALL COMPLY WITH ALL APPLICABLE NATIONAL, STATE, AND LOCAL CODES.

A diagram showing a long, thin rectangular structure. A horizontal double-headed arrow below the structure indicates a width of 64.75 (1644.7). The structure has a small gap in the middle, and there are small dots at the ends of the structure.

66.25 (1682.8)

POWER METER



01A	8-2-12	PIP	MRWA	A. UPDATED NOTE #5 & 8. B. ADDED NOTE #9.		09V098DW				
00A	2-24-11	MAV	KRKE	RELEASED TO PRODUCTION		09V098DW				
REV	DATE	BY	CHK	DESCRIPTION		ECN - R	CUST	SUP	OTH	

MODEL FILENAME		09V098DW/01.PRT	
CAD FILENAME/LAYERS		09V098DW_DC/01A.PRT	
 PANDUIT CORP TINLEY PARK, ILLINOIS			
VERTICAL, (12) L6-20R, METERED POWER OUTLET UNIT CUSTOMER DRAWING			
UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: INCHES X.X +/- 0.03 X.XX +/- 0.015 X.XXX +/- 0.005 [METRIC - MILLIMETER] X +/- 0.8 X.X +/- 0.4 X.XX +/- 0.13		UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE GIVEN IN INCHES, THIRD ANGLE PROJECTION	
DRAWN BY MAV	MAT'L:	SCALE NONE	
DATE 2-24-11		DRAWING NO. 09V098DW	DWG B
CHK'D KRKE			