

В

А

1. IDENTIFICATION: 1RU HORIZONTAL, (12) C-13, METERED 230V / 32A / SINGLE-PHASE POU COLOR

## BLACK

3. DIMENSIONS IN PARENTHESES ARE METRIC (mm).

4. POWER METER - RED, 4-DIGIT LED CONTINUOUSLY SCROLLS THROUGH POWER FACTOR, AMPS, VOLTS (RMS), AND REAL POWER IN WATTS (RMS).

В

А

5. UNIT COMPLIES WITH IEC 60950-1, EN55022, EN55024,

7. VISIT OUR ON-LINE CATALOG AT WWW.PANDUIT.COM FOR A CURRENT LIST OF PRODUCTS APPLICABLE FOR USE

8. MAXIMUM AVAILABLE POWER = 7.4 KW

P/N	WEIGHT					
112M1	8 lb (3.6 kg)					
6.50 [165.1]						
000						

	Ŭ	Ŭ	Ŭ	•	Ŭ	Ŭ	Ũ	Ű
)	0	0	0	⊕	0	0	0	•

09V098GY/00.PRT

09V098GY\_DC/00A.PRT

CORP TINLEY PARK, ILLINDIS 1RU HORIZONTAL, (12) C-13, METERED POWER OUTLET UNIT (HB1D2B2BM12M1)

CUSTOMER	DRAW	/ING
	<b>(</b>	

ISE SPECIFIED, DIMENSIONAL TOLERANCES AR   0.03 X. Y/2 0.8   0.015 X.X Y/2 0.8   0.005 X.X Y/2 0.13	CALCOD OTHERMEDE OF LETT	N IN
MAT'L:	SCALE NONE	
7	DRAWING NO.	DWG
	09V098GY	В
		6175