

1. IDENTIFICATION: VERTICAL, MIXED (18) C-13 & (6) C-19 NETWORKED 208V / 60A / 3-PHASE DELTA POU

4. CURRENT METER - RED, 4-DIGIT LED DISPLAY PROVIDES TRUE RMS CURRENT THAT CONTINOUSLY SCROLLS THROUGH THE THREE DIFFERENT MEASURED CIRCUITS. METER DISPLAYS CIRCUIT NAME FOLLOWED BY THE MEASURED CURRENT (E.G. CR-1 REPRESENTS PHASE 1). BREAKER LEVEL MONITORING CAN ALSO BE ACCESSED REMOTELY VIA ETHERNET CONNECTION.

В

7. VISIT OUR ON-LINE CATALOG AT WWW.PANDUIT.COM FOR A CURRENT LIST OF PRODUCTS APPLICABLE FOR USE

8. MAXIMUM AVAILABLE POWER = 17.3 KW

- 2.25 (57.2)

09V098UM/00.PRT		
09V098UM_DC/00A.PRT		
	TINLEY PARK, ILLI	NOIS
CAL, MIXED (18) C-13 & (6) C-19 NETWORKED POWER OUTLET UNIT (QZ1B2G6BN24R1) CUSTOMER DRAWING		
ISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: 0.03 [METRIC - WILLIMETER] X. +/- 0.8 0.015 X.X 0.005 X.X X.X +/- 0.13	UNLESS OTHERNISE SPECIFIED, ALL DIMENSIONS ARE GIVEN IN INCHES, THIRD ANGLE PROJECTION	
MAT'L: SCALE NONE		
	DRAWING NO.	DWG
-	09V098UM	В
-		SIZE