THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.



DETAIL A
(SCALE 4X)

PANDUIT P/N	WEIGHT
QZ1D2B2BM08W1	10 lb (4.5 kg)

NOTES:

1. IDENTIFICATION: VERTICAL, MIXED (4) C-13 & (4) C-19 NETWORKED 230V / 32A / SINGLE-PHASE POU

PART NO.	COLOR
QZ1D2B2BM08W1	BLACK

2. ACCESSORY COMPONENTS:
   (4) #10-32 x 1/2" MOUNTING SCREWS
   (4) #12-24 x 1/2" MOUNTING SCREWS
   (2) #10-32 LOCKING COLLAR SCREWS
   (2) L-BRACKETS
3. DIMENSIONS IN PARENTHESES ARE METRIC (mm).
4. CURRENT METER - RED, 4-DIGIT LED DISPLAY PROVIDES TRUE RMS CURRENT THAT CONTINOUSLY SCROLLS THROUGH THE THREE DIFFERENT MEASURED CIRCUITS. METER DISPLAYS CIRCUIT NAME FOLLOWED BY THE MEASURED CURRENT (E.G. CR-1 REPRESENTS PHASE 1). BREAKER/AGGREGATE CURRENT MONITORING CAN ALSO BE ACCESSED REMOTELY VIA ETHERNET CONNECTION.
5. UNIT COMPLIES WITH IEC 60950-1, EN55022, EN55024, AND IS CE MARKED.
6. RoHS COMPLIANT.
7. VISIT OUR ON-LINE CATALOG AT WWW.PANDUIT.COM FOR A CURRENT LIST OF PRODUCTS APPLICABLE FOR USE WITH THIS PART.
8. MAXIMUM AVAILABLE POWER = 7.4 KW





PLUG
32 AMP, 250V, SINGLE-PHASE
2P/3W
IEC 60309, SPLASHPROOF



FOUR (4)
RECEPTACLES
10 AMP, 250V
STRAIGHT BLADE
IEC 60320/C13



FOUR (4)
RECEPTACLES
16 AMP, 250V
STRAIGHT BLADE
IEC 60320/C19

REV	DATE	BY	CHK	DESCRIPTION	ECN - R	CUST	SUP	OTH
00A	11-24-10	MAV	KRKE	RELEASED TO PRODUCTION	09V098UK			

MODEL FILENAME: 09V098UK/00.PRT
CAD FILENAME/LAYERS: 09V098UK_Dc/00A.PRT

PANDUIT CORP TINLEY PARK, ILLINOIS

VERTICAL, MIXED (4) C-13 & (4) C-19 NETWORKED POWER OUTLET UNIT (QZ1D2B2BM08W1) CUSTOMER DRAWING

UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE:
INCHES: X.X +/- 0.03; X.XX +/- 0.015; X.XXX +/- 0.005
[METRIC - MILLIMETER]: X. +/- 0.8; X.X +/- 0.4; X.XX +/- 0.13
ANGLE +/- 1°

UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE GIVEN IN INCHES, THIRD ANGLE PROJECTION

DRAWN BY: MAV
MAT'L:
SCALE: NONE
DATE: 11-24-10
CHK'D: KRKE
DRAWING NO.: 09V098UK
DWG SIZE: B