

**Part Number:** 1062A

300V, (50 pr) 20 AWG (7x28) BC, (1) 22 AWG (7x30) BC,  
PVC/PVC, Foil Shld, PLTC-ER, CMG

## Product Description

Fifty 20 AWG pairs stranded (7x28) bare copper conductors plus one 22 AWG stranded (7x30) bare copper conductor, twisted pairs, PVC insulation, overall Beldfoil® shield (100% coverage), PVC jacket.

## Product Specifications

## Technical Specifications

### Construction and Dimensions

#### Conductor:

AWG	Stranding	Material	No. of Conductors	No. of Pairs
20	7x28	BC - Bare Copper		50
22	7x30	BC - Bare Copper	1	
Total Number of Conductors:			101	

#### Insulation:

Material
PVC - Polyvinyl Chloride

#### Color Chart 1:

Number	Color
1	Black & White and Numbered 1
2	Black & White and Numbered 2
3	Black & White and Numbered 3
4	Black & White and Numbered 4
5	Black & White and Numbered 5
6	Black & White and Numbered 6
7	Black & White and Numbered 7
8	Black & White and Numbered 8
9	Black & White and Numbered 9
10	Black & White and Numbered 10

11	Black & White and Numbered 11
12	Black & White and Numbered 12
13	Black & White and Numbered 13
14	Black & White and Numbered 14
15	Black & White and Numbered 15
16	Black & White and Numbered 16
17	Black & White and Numbered 17
18	Black & White and Numbered 18
19	Black & White and Numbered 19
20	Black & White and Numbered 20
21	Black & White and Numbered 21
22	Black & White and Numbered 22
23	Black & White and Numbered 23
24	Black & White and Numbered 24
25	Black & White and Numbered 25
26	Black & White and Numbered 26
27	Black & White and Numbered 27
28	Black & White and Numbered 28
29	Black & White and Numbered 29
30	Black & White and Numbered 30
31	Black & White and Numbered 31
32	Black&White and Numbered 32
33	Black & White and Numbered 33
34	Black & White and Numbered 34
35	Black & White and Numbered 35
36	Black & White and Numbered 36
37	Black & White and Numbered 37
38	Black & White and Numbered 38
39	Black & White and Numbered 39
40	Black & White and Numbered 40
41	Black & White and Numbered 41
42	Black & White and Numbered 42
43	Black & White and Numbered 43
44	Black & White and Numbered 44
45	Black & White and Numbered 45
46	Black & White and Numbered 46
47	Black & White and Numbered 47
48	Black & White and Numbered 48
49	Black & White and Numbered 49
50	Black & White and Numbered 50
Communication Wire	Orange

Cabling 1:

Lay Direction
Left Hand

Outershield 1:

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	Aluminum Foil-Polyester Tape	Beldfoil®	100 %	TC - Tinned Copper	20	7x28 mm

Outerjacket 1:

Material	Nominal Diameter	Nominal Wall Thickness	Ripcord
PVC - Polyvinyl Chloride	1.117 in	0.074 in	Yes

Print Legend:	LEGEND: BELDEN 1062A E34972 50PR20 1C22 SHIELDED (UL) CMG 105C OR PLTC OR ITC SUN RES DIR BUR OR AWM 2464 80C 300V OR C(UL) CMG ----FT4 IEEE 1202 (2 FT, 7 DIGIT SEQUENTIAL NUMBER) FEET
---------------	--

Electrical Characteristics

Conductor DCR:

Nominal Conductor DCR	Nominal Outer Shield DCR
9.5 Ohm/1000ft	6.5 Ohm/1000ft

Capacitance:

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Shield
30 pF/ft	55 pF/ft

Current:

Max. Recommended Current [A]
3 Amps per conductor @ 25°C

Inductance:

Nominal Inductance
0.19 µH/ft

Voltage:

UL Voltage Rating
300 V RMS (PLTC CMG)
150 V RMS (ITC)

Use

Suitability - Burial:	Yes
Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes
Suitability - Sunlight Resistance:	Yes
Max Recommended Pulling Tension:	1423 lbs

## Safety

C(UL) Flammability:	FT4
ICEA Flammability:	T-29-520
IEEE Flammability:	1202
UL Flammability:	UL1685 FT4 Loading

## Temperature Range

Operating Temp Range:	-30°C To +105°C
UL Temp Rating:	105°C

## Mechanical Characteristics

Min Bend Radius/Minor Axis:	11.5 in
-----------------------------	---------

## Part Number

Plenum (Y/N):	No
---------------	----

## Standards

CA Prop 65 (CJ for Wire & Cable):	CA Prop 65 (CJ for Wire & Cable)
CEC/C(UL) Specification:	CEC/C(UL) Specification
MII Order #39 (China RoHS):	MII Order #39 (China RoHS)
NEC/(UL) Specification:	NEC/(UL) Specification
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	EU CE Mark

## History

## Product Variants

Part Number	Color	Put-Up Type	Length
1062A 0102500	BLACK	Reel	2500 ft

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.