

Part Number: 83026

Hook-Up/Lead Wire UL AWM Style 1180, (1) 22 AWG

(19x34) SPC, TFE, 300V, 200°C

Product Description

One 22 AWG stranded (19x34) silver plated copper conductor, TFE insulation.

Product Specifications

Technical Specifications

Construction and Dimensions

Conductor:

| AWG | Stranding | Material | No. of Conductors |
|-----|-----------|----------------------------|-------------------|
| 22 | 19×34 | SPC - Silver Plated Copper | 1 |

| Total Number of Conductors: | 1 |
|-----------------------------|---|

Insulation:

| Material | Nominal Wall Thickness |
|---------------------------|------------------------|
| TFE - Tetrafluoroethylene | 0.015 in |

Outerjacket 1:

| Nominal Diameter | |
|------------------|--|
| 0.06 in | |

Electrical Characteristics

Conductor DCR:

| Nominal Conductor DCR | |
|-----------------------|--|
| 15.75 Ohm/1000ft | |

Current:

| Element | Max. Recommended Current [A] |
|---------------------------------------|------------------------------|
| Mil-Std-975M Table 3.16 (single wire) | 4.5 amps |

Voltage:

| Description | UL Description | UL Voltage Rating | Voltage Rating [V] |
|---------------|----------------|-------------------|--------------------|
| Mil-W-16878/5 | UL AWM 1180 | 300V RMS | 1000 V RMS |

Use

Safety

| , | UL Flammability: | VW-1 |
|---|------------------|------|

Temperature Range

| Operating Temp Range: | -70°C To +200°C |
|-----------------------|-----------------|

Mechanical Characteristics

Part Number

| Plenum (Y/N): | l No | |
|---|------|--|
| *************************************** | 1 | |

Standards

| CA Prop 65 (CJ for Wire & Cable): | CA Prop 65 (CJ for Wire & Cable) | |
|-----------------------------------|----------------------------------|--|
| MII Order #39 (China RoHS): | MII Order #39 (China RoHS) | |
| MIL Spec Rating: | MIL Spec Rating | |
| Military Specification: | Military Specification | |
| UL Rating: | UL Rating | |
| EU Directive Compliance: | EU Directive 2003/11/EC (BFR) | |
| EU CE Mark: | EU CE Mark | |

History

Product Variants

| Part Number | Color | Put-Up Type | Length |
|---------------|-------------|-------------|---------|
| 83026 0011000 | BROWN | Reel | 1000 ft |
| 83026 001100 | BROWN | Reel | 100 ft |
| 83026 0021000 | RED | Reel | 1000 ft |
| 83026 002100 | RED | Reel | 100 ft |
| 83026 0031000 | ORANGE | Reel | 1000 ft |
| 83026 003100 | ORANGE | Reel | 100 ft |
| 83026 0041000 | YELLOW | Reel | 1000 ft |
| 83026 004100 | YELLOW | Reel | 100 ft |
| 83026 0051000 | GREEN, DARK | Reel | 1000 ft |
| 83026 005100 | GREEN, DARK | Reel | 100 ft |
| 83026 0061000 | BLUE, LIGHT | Reel | 1000 ft |
| 83026 0071000 | VIOLET | Reel | 1000 ft |
| 83026 007100 | VIOLET | Reel | 100 ft |
| 83026 0081000 | GRAY | Reel | 1000 ft |
| 83026 0091000 | WHITE | Reel | 1000 ft |
| 83026 009100 | WHITE | Reel | 100 ft |
| 83026 0101000 | BLACK | Reel | 1000 ft |
| 83026 010100 | BLACK | Reel | 100 ft |

© 2016 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/96/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.