

#### 18" ABS WAP Lock-box: T-bar, Translucent door

Category: Wall and Hard Ceiling - Surface Mount - Surface Mount - Enclosures



Non-metallic enclosure secures and protects WAPs, wireless routers, and multiple networking components in offices, hotels, retail locations and other indoor venues. This rugged polycarbonate plastic enclosure is virtually transparent to wireless signals so WAPs with integrated antennas or small detachable antennas may be protected. The box can be mounted directly over the telecom outlet, and power strip and cabling can be neatly concealed. Cable raceway or conduit can be conveniently terminated.











#### **Features & Benefits**

- Accommodates most vendors' enterprise access points with external antennas
- · Locking, fully-hinged door
- Simplify code, industry directives, policy, and aesthetics compliance

## **Technical Specifications**

- Design: Wireless access point enclosure designed to be surface mounted on hard-lid ceilings or walls. Designed to accommodate cable modems, wireless routers, and wireless access points with integrated or non-detachable antennas and external antennas from most vendors.
- Performance: Ventilated, paintable, impact-resistant polycarbonate plastic enclosure is virtually transparent to wireless signals
- Oberon Skybar-shaped locking, fully-hinged door, keyed alike
- Universal T-bar for most vendors' access points
- Opening in back allows for placement directly over outlet
- Twistouts in sidewalls for conduit or raceway
- Construction: UL 94-V0 Classified polycarbonate. Body is white, door is translucent, frosted
- Size: 12 inches by 18 inches by 5.15 inches (305mm by 457 mm by 131 mm)

## **Configurations**

Please specify configuration when ordering.

Model Number	Description
1016	18" ABS WAP Lock-box: Solid door
1016-C	18" ABS WAP Lock-box: T-bar, Translucent door

#### **Measurements** (Maximum values):

- Height: 12 in.
- Width: 18 in.
- Depth: 5 in.
- Item Weight: 5 lbs.
- Shipping Weight: 6 lbs.

### **Includes**

- (1) Unit
- (1) Internal universal access point mounting T-bar bracket
- T-bar spacer kit
- (10) Plastic cable tie downs
- 100 inches of Velcro strap
- (2) Keys for lock
- (2) 1/2" Nylon spacer
- (2) #6 x 7/8" screw
- (2) #6 x 1/4 screw
- Installation instructions

#### **Documentation Links**

- Spec Sheet oberoninc.com/index.php?option=com\_content&view=article&id=1305&ltemid=399
- Installation Instructions oberoninc.com/images/WebDocs/Model1016-00\_Installation\_Instructions.pdf
- Customer Prints oberoninc.com/images/WebDocs/Model1016\_Customer\_Print.pdf
- App Note Wireless Coverage FAQ oberoninc.com/images/WebDocs/Application\_Note\_Wireless\_Coverage\_FAQ.pdf
- Positioning the Wireless Router oberoninc.com/images/WebDocs/Positioning\_your\_wireless\_router\_with\_Oberon\_Network\_Cabinet.pdf
- SECTION 27\_21\_33 DATA COMMUNICATIONS WIRELESS ACCESS POINTS -

http://oberoninc.com/images/WebDocs/SECTION 27\_21\_33 DATA COMMUNICATIONS WIRELESS ACCESS POINTS.pdf

Images and documents may depict similar models in the product series.

# **Dimensional Images**



