

SAFE STEP EDGE SEALER

Page: 1

Compilation date: 06/09/2013

Revision No: 1

## Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: SAFE STEP EDGE SEALER

Product code: 43542

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants.

## 1.3. Details of the supplier of the safety data sheet

Company name: ROCOL

ROCOL House Swillington Leeds

West Yorkshire LS26 8BS

ENGLAND

**Tel:** +44 (0) 113 232 2700 **Fax:** +44 (0) 113 232 2740

Email: <a href="mailto:customer-service@rocol.com">customer-service@rocol.com</a>

## 1.4. Emergency telephone number

Emergency tel: +44 (0) 113 232 2600

## **Section 2: Hazards identification**

### 2.1. Classification of the substance or mixture

Classification under CHIP: F: R11; Xi: R36; -: R66; -: R67

Most important adverse effects: Highly flammable. Irritating to eyes. Repeated exposure may cause skin dryness or

cracking. Vapours may cause drowsiness and dizziness.

## 2.2. Label elements

Label elements under CHIP:

Hazard symbols: Highly flammable.

Irritant.





Risk phrases: R11: Highly flammable.

R36: Irritating to eyes.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

## SAFE STEP EDGE SEALER

Page: 2

Safety phrases: S9: Keep container in a well-ventilated place.

S16: Keep away from sources of ignition - No smoking.

S25: Avoid contact with eyes.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek

medical advice.

S37: Wear suitable gloves.

S51: Use only in well-ventilated areas.

### 2.3. Other hazards

PBT: This substance is not identified as a PBT substance.

### Section 3: Composition/information on ingredients

#### 3.2. Mixtures

### **Hazardous ingredients:**

#### **ACETONE**

EINECS	CAS	CHIP Classification	CLP Classification	Percent
200-662-2	67-64-1	F: R11; Xi: R36; -: R66; -: R67	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336: -: EUH066	70-90%

### Section 4: First aid measures

### 4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin.

Drench the affected skin with running water for 10 minutes or longer if substance is still

on skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist

examination.

Ingestion: Wash out mouth with water. Do not induce vomiting. Transfer to hospital as soon as

possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Seek

medical attention if you feel unwell.

## 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. Corneal burns may occur.

Ingestion: Nausea and stomach pain may occur. There may be vomiting. Convulsions may occur.

There may be loss of consciousness.

Inhalation: Exposure may cause coughing or wheezing. There may be congestion of the lungs

causing severe shortness of breath. There may be loss of consciousness. Convulsions

may occur.

SAFE STEP EDGE SEALER

Page: 3

## 4.3. Indication of any immediate medical attention and special treatment needed

### Section 5: Fire-fighting measures

### 5.1. Extinguishing media

Extinguishing media: Carbon dioxide. Dry chemical powder.

## 5.2. Special hazards arising from the substance or mixture

Exposure hazards: Highly flammable. In combustion emits toxic fumes.

### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

#### Section 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Eliminate all sources of

ignition. Turn leaking containers leak-side up to prevent the escape of liquid.

#### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

## 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Mix with sand or vermiculite. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

## 6.4. Reference to other sections

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Smoking is forbidden.

## 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from

sources of ignition.

Suitable packaging: Must only be kept in original packaging.

### 7.3. Specific end use(s)

## Section 8: Exposure controls/personal protection

## 8.1. Control parameters

SAFE STEP EDGE SEALER

Page: 4

### Hazardous ingredients:

#### **ACETONE**

## Workplace exposure limits:

## Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1210 mg/m3	3620 mg/m3	-	-

### 8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical

equipment are not a source of ignition.

Respiratory protection: Gas/vapour filter, type A: organic vapours (EN141).

Hand protection: Gloves (solvent-resistant). Nitrile gloves.

**Eye protection:** Safety glasses with side-shields. Ensure eye bath is to hand.

Skin protection: Solvent resistant protective clothing.

### Section 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Odour: Pungent

Solubility in water: Miscible

Also soluble in: Ethanol. Diethyl ether.

Viscosity: Highly viscous

Kinematic viscosity: 3600 cps

Viscosity test method: Kinematic viscosity in 10-6 m2/s at 40°C (ISO 3104/3105)

Boiling point/range°C: 56 Flash point°C: -18

Relative density: 0.84-0.862

### 9.2. Other information

Other information: Not applicable.

## Section 10: Stability and reactivity

### 10.1. Reactivity

# 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

### 10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

SAFE STEP EDGE SEALER

Page: 5

### 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

## **Section 11: Toxicological information**

## 11.1. Information on toxicological effects

#### Relevant effects for mixture:

Effect	Route	Basis
Irritation	OPT	Hazardous: calculated

## Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. Corneal burns may occur.

Ingestion: Nausea and stomach pain may occur. There may be vomiting. Convulsions may occur.

There may be loss of consciousness.

Inhalation: Exposure may cause coughing or wheezing. There may be congestion of the lungs

causing severe shortness of breath. There may be loss of consciousness. Convulsions

may occur.

## **Section 12: Ecological information**

# 12.1. Toxicity

Ecotoxicity values: Not applicable.

### 12.2. Persistence and degradability

Persistence and degradability: No data available.

# 12.3. Bioaccumulative potential

# 12.4. Mobility in soil

Mobility: Readily absorbed into soil.

### 12.5. Results of PBT and vPvB assessment

PBT identification: This substance is not identified as a PBT substance.

# 12.6. Other adverse effects

Other adverse effects: No data available.

### Section 13: Disposal considerations

## 13.1. Waste treatment methods

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## SAFE STEP EDGE SEALER

Page: 6

### **Section 14: Transport information**

14.1. UN number

UN number: UN1133

14.2. UN proper shipping name

Shipping name: ADHESIVES

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: ||

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

**Tunnel code:** D/E **Transport category:** 2

### Section 15: Regulatory information

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

### **Section 16: Other information**

#### Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

Compiled in accordance with REACH.

Phrases used in s.2 and 3: EUH066: Repeated exposure may cause skin dryness or cracking.

H225: Highly flammable liquid and vapour.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

R11: Highly flammable. R36: Irritating to eyes.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.

[final page]