

Pretium EDGE® Adapter Panel, LC Duplex

12 fibres, Single-Mode (OS2)

CORNING

Pretium EDGE® LC duplex adapter panels provide a simple interface to mate LC connectors. This occurs when connecting LC trunks to harnesses, and when connecting LC trunks to LC patchcords.

Features and Benefits

Can be installed or removed from the front or rear of a housing

Packaged in easy-open containers



Specifications

General Specifications

Application	Data Centre LAN/SAN, Data Centre
Product Type	Panels & Modules
Fibre category	SM (OS2)

Design - Hardware

Housing Material	Composite
Housing Colour	black
Connector Type	LC Duplex
Fibre Count	12
Number of Adapters per Panel	6

Mechanical Characteristics

Dimensions (W x D x H)	100 mm x 124 mm x 12 mm
Weight	0.028 kg

Pretium EDGE® Adapter Panel, LC Duplex

12 fibres, Single-Mode (OS2)

CORNING

Design Adapter

Adapter Type	LC Duplex
Adapter Housing Material	Composite
Adapter Housing Colour	blue
Adapter Style	Shuttered LC

Chemical characteristics

RoHS	Free of hazardous substances according to RoHS 2002/95/EG
------	---

Ordering Information

Part Number	EMOD-CP12-AE
Product Description	12 fibre LC duplex adapter panel, blue, adapter for Single-Mode (OS2)

Shipping Information

Packing dimensions (L x W x H)	250 mm x 130 mm x 200 mm
Shipping Weight	0.715 kg
Units per Delivery	1/1



Corning Optical Communications GmbH & Co. KG · Leipziger Strasse 121 · 10117 Berlin, GERMANY

00 800 2676 4641 · FAX: +49 30 5303 2335 · www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2014 Corning Optical Communications. All rights reserved.