THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.




REAR VIEW




FRONT VIEW

| PANDUIT P/N | WEIGHT |
|---|---|
| Q1L2B2G6N24AFA0 | X.XXkg (XX.Xlb) |

NOTES:

1. IDENTIFICATION: VERTICAL, MIXED (18) C13 LOCKING, (6) C19 LOCKING NETWORK-ENABLED MONITORED WITH MONITORED AND SWITCHED PER OUTLET, 208V / 60A / THREE-PHASE DELTA PDU

| PART NO. | COLOR |
|---|---|
| Q1L2B2G6N24AFA0 | BLACK |

2. ACCESSORY COMPONENTS:
   (1) QUICK-START GUIDE
3. PRIMARY DIMENSIONS ARE IN MILLIMETERS, SECONDARY DIMENSIONS IN [ INCHES ]
4. PHASE (L1, L2, L3) LEVEL POWER (AMPS, VOLTS, kWh, kVA, POWER FACTOR, FREQUENCY) MONITORING. DATA CAN BE ACCESSED ON UNIT DISPLAY OR REMOTELY WHEN CONNECTED VIA ETHERNET CONNECTION
5. OUTLET LEVEL POWER (AMPS, VOLTS, POWER FACTOR, FREQUENCY) MONITORING CAN BE ACCESSED REMOTELY VIA ETHERNET CONNECTION
6. INDIVIDUAL RECEPTACLES CAN BE SWITCHED ON/OFF REMOTELY
7. RoHS COMPLIANT
8. VISIT OUR ON-LINE CATALOG AT WWW.PANDUIT.COM FOR A CURRENT LIST OF PRODUCTS APPLICABLE FOR USE WITH THIS PART
9. MAXIMUM AVAILABLE INPUT POWER = 17.3 kW
10. INSTALLATION SHALL COMPLY WITH ALL APPLICABLE NATIONAL, STATE, AND LOCAL CODES
11. PRINTED WITH PHASE & CIRCUIT IDENTIFICATION




SIDE VIEW



PLUG
60 AMP, 250V X 3~DELTA
3P/4W
IEC 60309, SPLASHPROOF



EIGHTEEN (18)
LOCKING RECEPTACLES
15 AMP, 250V
STRAIGHT BLADE
IEC 60320/C13




SIX (6)
LOCKING RECEPTACLES
20 AMP, 250V
STRAIGHT BLADE
IEC 60320/C19

| REV | DATE | BY | CHK | APR | DESCRIPTION | ECN |
|---|---|---|---|---|---|---|
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| 03A | 2-6-15 | MRWA | GLM | EDM | RELEASED TO PRODUCTION | 12V091SB |

WE ASK THAT YOU CHECK FULLY THE DIMENSIONS, NOTES, AND SIGN THE CLIENT SIGNATUTE BOX.

THE JOB WILL NOT PROGRESS WITHOUT SIGNED APPROVAL. PLEASE DO NOT DELAY IN RETURNING PROOF AS IT WILL AFFECT DELIVERY.

SIGN

DATE

PRINT

TITLE
SMARTZONE NETWORK-ENABLED MSPO SERIES RACK PDU
Q1L2B2G6N24AFA0
CUSTOMER DRAWING

ITEM REVISION NAME
12V091SB/03.PRT

DATASET FILE NAME
12V091SB_DC/03A.PRT

UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE:

| INCHES | | METRIC - MILLIMETER | | ANGLE |
|---|---|---|---|---|
| X.X | +/- | X. | +/- | +/- |
| X.XX | +/- | X.X | +/- | |
| X.XXX | +/- | X.XX | +/- | |

THIRD ANGLE PROJECTION

MATERIAL/COLOR:
N/A

DRAWING NUMBER:
12V091SB_DC

| DRAWN BY | DATE | CHK | SCALE | SIZE |
|---|---|---|---|---|
| MRWA | 2-6-15 | GLM | NTS | B |

SHT 1 OF 1