

1		
PANDUIT P/N	WEIGHT	
Q1S2B2G6N24AFA0	X.XXkg (XX.XIb)	
NETWORK-E Switched.	MIXED (18) C13 (6) C19 LOCKING, NABLED MONITORED 208V / 60A / SE DELTA PDU	
<u>NO.</u> <u>Color</u> 2g6n24afao Black		
CAN BE ACCESSED ON L ELY WHEN CONNECTED V IDUAL RECEPTACLES CA ELY COMPLIANT OUR ON-LINE CATALOG CURRENT LIST OF PRO ITH THIS PART UM AVAILABLE INPUT F	INCHES J POWER (AMPS, VOLTS, REQUENCY) MONITORING. JNIT DISPLAY OR (IA ETHERNET CONNECTION N BE SWITCHED ON/OFF AT WWW.PANDUIT.COM DUCTS APPLICABLE FOR POWER = 17.3 kW (WITH ALL APPLICABLE L CODES	B
(10 FOOT) POWER CORD [3.		
<u>side view</u>		
E ASK THAT YOU CHECK FULLY THE IMENSIONS, NOTES, AND SIGN THE CLIE IGNATUTE BOX. HE JOB WILL NOT PROGRESS WITHOUT IGNED APPROVAL. PLEASE DO NOT DELAY N RETURNING PROOF AS IT WILL AFFECT ELIVERY.	NT DATE PRINT	A
SMARTZONE NETWORK-EN	ABLED MS SERIES RACK PDU	
	G6N24AFAO /er drawing	
TEM REVISION NAME 12V091QQ/03.PRT		
ATASET FILE NAME 12V091QQ_DC/03A.PR		
NLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLER NCHES METRIC - MILLIMETEF XX +/- X.X +/- XXX +/- X.XX +/-		
THIRD AI PROJECT		
MRWA 2-6-15 GLM 1 1	NTS SHT 1 OF 1	

1

\_