

CCH Pigtailed Splice Cassette

12 F, LC APC duplex, Single-mode (OS2), single-fiber (250 µm)

CORNING

CCH pigtailed splice cassettes enable faster field splicing and easy modular management of connectorization within the housing.

The CCH pigtailed splice cassettes are preloaded and pre-routed for quick fusion splicing of either individual or ribbon fiber pigtails, using the same space-saving platform as the standard CCH splice cassette.

The pre-routed pigtailed cassettes reduce field labor by streamlining the features and components of the pigtail cassette to allow for efficiencies in the field. They are prepped with a 2 meter pigtail assembly with all pre-existing CCH panel connector options. The pigtailed cassettes have 900 µm at the connector panel for added durability and colored 250 µm for ease of splicing as well as having strain relief pre-applied to the assemblies from the manufacturing facility.

With the pigtailed cassette, the field will also enjoy the elimination of individual splice trays or separate splice housings, as well as allowing splicing to be done away from the rack housing in a suitable workspace as needed. The modular design makes it easy to access the fiber in an individual cassette without disturbing the other fibers in the housing.

Each cassette is shipped with the pigtailed CCH adapter panel of choice, one rail for use with CCH-01U/2U/3U housings, and two rails used with CCH-04U housings. Grommets and cable ties for additional strain relief and protective braided tubing for incoming cable are also included. Splicing cassettes ship with the appropriate quantity and type of heat-shrink splice protectors.

Many of our fiber optic hardware products are highly configurable. If you don't see what you are looking for here, please review the ordering matrix contained in the family spec sheet found on the right, or contact Customer Care at 1-800-743-2675.



Features and Benefits

Manage cable slack for a CCH panel in a modular footprint

Fast, easy and reliable initial routing, and quick, simple reaccess for moves, adds and changes (MACs)

Includes everything needed to convert a CCH housing for modular routing and/or splicing

Easy ordering and field installation

Modular splice capability

Manage all splices inside the housing

CCH Pigtailed Splice Cassette

12 F, LC APC duplex, Single-mode (OS2), single-fiber (250 µm)

CORNING

Features and Benefits

900 µm jacket at the connector panel

Added fiber protection at the connector

Colored 250 µm at splice point

Easy to identify and prep colored 250 µm for fast and easy splicing

Pre-prepped splice cassette

Saves time in the field with a ready to splice product

Standards

Approvals and Listings

Meets ANSI/TIA/EIA-568A and 606

Specifications

General Specifications	
Application	Enterprise Networks, Data Center
Product Type	Rack-Mountable Hardware
Mounting Type	CCH Housings, Wall-Mountable
Cable Type	250 µm
Fiber Category	Single-mode (OS2)
Technology	Fusion Splice

Design - Hardware	
Connector Configuration	LC duplex
Connector Polish	APC
Fiber Count	12
Panel or Module Type	CCH
Splice Protectors Type	Single fiber Heat-shrink
Number of Splice Protectors	12

Mechanical Characteristics	
Dimensions (L x W x D)	6.4 in x 1.4 in x 7.9 in 162.0 mm x 35.0 mm x 200.0 mm

CCH Pigtailed Splice Cassette

12 F, LC APC duplex, Single-mode (OS2), single-fiber (250 µm)

CORNING

Design Adapter

Adapter Type	LC duplex
--------------	-----------

Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

Ordering Information

Part Number	CCH-CS12-B3-P00RE
Product Description	CCH Pigtailed Splice Cassette, 12 F, LC APC duplex, Single-mode (OS2), single-fiber (250 µm)
EAN Code	4056418151359

Shipping Information

Units per Delivery	1/1
Dimensions (HxWxD)	5 cm x 20.3 cm x 36.8 cm (2 in x 8 in x 14.5 in)



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2016 Corning Optical Communications. All rights reserved.

CORNING