

MANUAL INTERCOM SYSTEMS

KB-LC-2 – Single Channel Master

Description

The **KB-LC-2** is a durable, reliable solution for any single-channel application where the Master does not need to talk hands-free

Features

- · Master presses one button to talk
- · Sub-station speaks hands-free
- Completely self-contained—no separate junction box or amplifier
- · Connect multiple speakers in parallel



Construction: Vinyl coated Steel

Dimensions: 10.50(267) W x 3.13(80) H x 8.75(222) D in(mm)

Weight: 7 lbs. (3.2kg)

Mounting: Designed for desk mounting

Power: 120VAC required for 24VDC, 600mA power supply

Cable: 1 shielded pair needed for all sub-stations

Options & Accessories

Paging Booster: Model **K-HP-50** provides 50 watts of power

Annunciation: Order model KB-LC-2W for a single-channel intercom with annunciation tones and lights

which identify calling stations

Sub-Stations

With Call Button: Model K-LR-3W flush mounts—use K-SM-L accessory to surface mount. Model K-LR-3

is a desk-style version of K-LR-3W

Without Call Button: Model K-LR-2R flush mounts—use K-SM accessory to surface mount. Model K-LR-2 is a

desk-style version of K-LR-2R

Cradle Phone: Model K-S-112X provides clear communication and privacy in a noisy environment. Use

with model K-C-20 horn speaker so master can call person at cradle phone location. Horn

disconnects when cradle phone is picked up

Horn Speaker: Model K-C-20 furnishes up to 4 times the volume of sub-station K-LR-2R. Model K-C-20V

includes built-in volume control

High-Powered: Model **K-HP-3** is a 5 watt speaker for indoor use. Model **K-HP-3V** includes built-in volume

control

Ceiling Speaker: Model **S-8318B** is an 8" ceiling speaker with white metal baffle and built-in volume control.

For indoor use

Gas Dispenser: Model **S-8304** is a built-in speaker for gas dispensers. No call origination or volume

control



Rev. 10/25/10

KB-LC-2 – Single Channel Master

Dimensions



