

# Open-Access™ Cable Management System

# PANDUIT®

SPECIFICATION SHEET

## specifications

Cable management solutions shall be capable of managing cable on the front and rear of any standard EIA 19" rack or cabinet. Panels shall be constructed of a steel panel with plastic D-rings attached. Horizontal D-rings shall snap into panels and vertical D-rings shall be screw mounted to rack. Horizontal panels shall have pass-through holes and shall be available in both front and rear versions and front only versions.



| Part Number | RU | Height in (mm) | Width in (mm) | Depth in (mm) |
|-------------|----|----------------|---------------|---------------|
| CMPHF1      | 1  | 1.7 (43)       | 19 (482)      | 3.4 (87)      |
| CMPHF2      | 2  | 3.5 (88)       | 19 (482)      | 3.4 (87)      |
| CMPHHF1     | 1  | 1.7 (43)       | 19 (482)      | 5.4 (137)     |
| CMPHH2      | 2  | 3.5 (88)       | 19 (482)      | 5.4 (137)     |
| CMPH1       | 1  | 1.7 (43)       | 19 (482)      | 8.6 (218)     |
| CMPH2       | 2  | 3.5 (88)       | 19 (482)      | 8.6 (218)     |

## technical information

|                                 |   |
|---------------------------------|---|
| <b>D-ring mounting options:</b> | Horizontal D-rings snap into Open-Access™ panels only; vertical D-rings screw into EIA racks              |
| <b>Panel mounting options:</b>  | Mount to any EIA 19" rack or cabinet  |
| <b>Packaging:</b>               | Cable management panels include horizontal D-rings pre-installed onto panels and #12-24 mounting hardware |

## key features and benefits

|   |   |
|---|---|
| <b>Modular, snap-in D-rings</b>           | Provides flexibility for system requirements              |
| <b>Flexible D-rings</b>                   | Allows easy access to cables for moves, adds, and changes |
| <b>Rounded D-rings</b>                    | Prevents cable snags                                      |
| <b>Cable pass-through holes on panels</b> | Provides ease of installation and cable maintenance       |
| <b>Available in a variety of styles</b>   | Suitable for large and small cabling installations        |
| <b>Lightweight, sturdy construction</b>   | Easy to work with while still providing durability        |
| <b>Optional snap-on cover</b>             | Provides an aesthetically pleasing solution               |

## applications

Panduit® Open-Access™ Cable Management components offer an economical cable management solution for current and future applications. D-rings provide an "open" and efficient way to manage cable on any standard EIA 19" rack or cabinet. The panels can be used in multimedia applications with all coax, copper and fiber optic cables

The Open-Access™ System offers increased flexibility due to the modularity of the D-rings. Components can be easily added as system requirements grow, providing the lowest installed cost. The Open-Access™ Cable Management System can be used with Mini-Com® Modular Patch Panels, Opticom® Enclosures and NetRunner™ Vertical Cable Management and Racks for a total system solution now and in the future.

### Open-Access™ Cable Management System

#### 2 Rack Space Panel, Front and Rear

19" 3 x 3 D-rings on front and 3 x 5 D-rings on rear: CMPH2

#### 2 Rack Space Panel, Front Only

19" 3 x 3 D-rings: CMPHF2  
19" 3 x 5 D-rings: CMPHH2

#### 2 Rack Space Panel, Front and Rear

19" 1.5 x 3 D-rings on front and 1.5 x 5 on rear: CMPH1

#### 1 Rack Space Panel, Front Only

19" 1.5 x 3 D-rings: CMPHF1  
19" 1.5 x 5 D-rings: CMPHHF1

#### 2 Rack Space Horizontal D-Rings

3 x 3: CMDRH2

#### 1 Rack Space Horizontal D-Rings

1.5 x 3: CMDRH1

#### Vertical D-Rings

2 RU: CMVDR2  
1 RU: CMVDR1  
Center: CMVDRC

#### Covers

19" 2 RU: CMPH2C  
19" 1 RU: CMPH1C

# Open-Access™ Cable Management System



**CMPH1**



**CMPH2**



**CMPHF1**



**CMPHF2**



**CMPHHF1**



**CMPHH2**



**CMDRHD2**



**CMVDR2**

| Part Number    | Front              |                          |                          |                         |                         | Rear               |                          |                          |                         |                         |
|----------------|--------------------|--------------------------|--------------------------|-------------------------|-------------------------|--------------------|--------------------------|--------------------------|-------------------------|-------------------------|
|                | Channel Area (in²) | Cat. 6A (28AWG - 0.185") | Cat. 6A (24AWG - 0.275") | Cat. 6 (28AWG - 0.150") | Cat. 6 (24AWG - 0.235") | Channel Area (in²) | Cat. 6A (28AWG - 0.185") | Cat. 6A (24AWG - 0.275") | Cat. 6 (28AWG - 0.150") | Cat. 6 (24AWG - 0.235") |
| <b>CMPH1</b>   | 2.2                | 32                       | 14                       | 49                      | 20                      | 2.9                | 43                       | 19                       | 65                      | 26                      |
| <b>CMPHF1</b>  |                    |                          |                          |                         |                         | -                  | -                        | -                        | -                       | -                       |
| <b>CMPH2</b>   | 5.9                | 87                       | 39                       | 133                     | 54                      | 10.9               | 161                      | 73                       | 245                     | 100                     |
| <b>CMPHF2</b>  |                    |                          |                          |                         |                         | -                  | -                        | -                        | -                       | -                       |
| <b>CMPHH2</b>  | 10.9               | 161                      | 73                       | 245                     | 100                     | -                  | -                        | -                        | -                       | -                       |
| <b>CMPHHF1</b> | 2.9                | 43                       | 19                       | 65                      | 26                      | -                  | -                        | -                        | -                       | -                       |

## WORLDWIDE SUBSIDIARIES AND SALES OFFICES

PANDUIT CANADA  
Markham, Ontario  
cs-cdn@panduit.com  
Phone: 800.777.3300

PANDUIT EUROPE LTD.  
London, UK  
cs-emea@panduit.com  
Phone: 44.20.8601.7200

PANDUIT SINGAPORE PTE. LTD.  
Republic of Singapore  
cs-ap@panduit.com  
Phone: 65.6305.7575

PANDUIT JAPAN  
Tokyo, Japan  
cs-japan@panduit.com  
Phone: 81.3.6863.6000

PANDUIT LATIN AMERICA  
Guadalajara, Mexico  
cs-la@panduit.com  
Phone: 52.33.3777.6000

PANDUIT AUSTRALIA PTY. LTD.  
Victoria, Australia  
cs-aus@panduit.com  
Phone: 61.3.9794.9020

For a copy of Panduit product warranties, log on to [www.panduit.com/warranty](http://www.panduit.com/warranty)

For more information

Visit us at [www.panduit.com](http://www.panduit.com)

Contact Customer Service by email: [cs@panduit.com](mailto:cs@panduit.com)  
or by phone: 800.777.3300

**PANDUIT®**

©2016 Panduit Corp.  
ALL RIGHTS RESERVED.  
RKSP140--WW-ENG  
Replaces WW-RKSP18  
4/2016