

ISP-RSC3-110S LSN shutter door contact

www.boschsecurity.com



BOSCH

Invented for life



- ▶ LSN shutter door contact for monitoring shutter, sliding, and garage doors
- ▶ Tamper surveillance
- ▶ High level of mechanical strength
- ▶ Parallel mounting
- ▶ VdS class C, EN 50131-2-6 Grade 3

The LSN shutter door contact is used to monitor shutter, sliding, and garage doors.

The contact is equipped with tamper surveillance. If an external magnet is in close proximity, the tamper switch is activated, which generates a tamper alarm. The shutter door contact consists of a sealed magnetic switch and a magnet in a plastic housing. The components are surface-mounted parallel to each other. The magnetic switch is mounted on the floor.

Certifications and approvals

Region	Certification	
Germany	VdS	G113048
Europe	CE	ISP-RSC3-110S
	EN50131	ISP-RSC3-110S

Installation/configuration notes

Installation information

- For doors < 1.5 m, one shutter door contact is required. For doors > 1.5 m, use two shutter door contacts. Take note of the permissible installation tolerances.

- The connection cable is protected over a length of 1 m by a metal tube.
- The magnetic switch is installed at ground level (requires a flat surface). The switch will not be damaged if driven over by vehicles with rubber tires.
- Only anti-magnetic screws may be used for installation.
- The magnetic switch must not be used as a door stopper.

Connecting LSN contacts


- Each LSN contact is a physical LSN element (1 out of 127 possible per loop).
- The length of LSN contact connection cables must be included when planning the total line length of the LSN loop, as the LSN technology is integrated in these contacts.
- Passive elements for connecting the connection cables to the installation cable must be positioned as close as possible to the LSN contacts, as a 1-m connection cable with 2-m LSN cable length is included in the calculation of the LSN cable length (LSN is fed into the contacts and back out again).
- Connector boxes (optional) are classified as installation material.

LSN (Local Security Network)

In the event of wire breakage or short-circuits, all LSN elements in the LSN loop continue to be monitored. In this case, the system automatically creates two stub lines that continue to monitor from both sides up to the location of the fault.

Testing LSN contacts

- Reed switch and microswitch functions can be checked before installation using a high-Ohm multimeter or continuity checker (for diode paths).
- The resistance values are approximate values; a large change in resistance is significant.



- | | |
|---|-------------------------------------------------------------------------------------------|
| 1 | Contact us |
| 2 | High-ohm multimeter
- Contact open: approx. 3 MOhm
- Contact closed: approx. 1 MOhm |

Only the intrusion contact can be checked in this way. The tamper switch can be checked in conjunction with the LSN control panel or with the LSN testing device (software version 3.x onward).

Parts included

Type	Qty.	Components
ISP-RSC3-110S	1	Shutter door contact with 4-m connection cable and magnet incl. installation materials and metal tube

Technical specifications

LSN operating voltage	15 V to 33 V
Reed contact type	Normally open contact
Switch tolerance	$\geq 10^7$
Installation distance	≥ 25 mm
Magnetic material	AlNiCo 500
Temperature range	-25 °C to +70 °C
Connection cable	LiY(St)Y 4 x 0.22 mm ² , white
Cable length	4 m
Cable protection tube	Flexible metal tube, diameter: 6/9 mm, covered in plastic, length: 1 m, color: gray
Housing material/color	Plastic/gray
Weight (with cable and magnet)	Approx. 285 g
Switch dimension	150 x 40 x 13.5 mm
Magnet dimension	65 x 42 x 35 mm

Protection category	IP67
Environmental class VdS/EN	III/III A

Ordering information

ISP-RSC3-110S LSN shutter door contact

For monitoring shutter, sliding, and garage doors, tamper surveillance

Order number **ISP-RSC3-110S**

Represented by:

Americas:

Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5617 BA Eindhoven, The Netherlands
Phone: + 31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security
Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

China:

Bosch (Shanghai) Security Systems Ltd.
201 Building, No. 333 Fuquan Road
North IBP
Changning District, Shanghai
200335 China
Phone +86 21 22181111
Fax: +86 21 22182398
www.boschsecurity.com.cn

America Latina:

Robert Bosch Ltda Security Systems Division
Via Anhanguera, Km 98
CEP 13065-900
Campinas, Sao Paulo, Brazil
Phone: +55 19 2103 2860
Fax: +55 19 2103 2862
latam.boschsecurity@bosch.com
www.boschsecurity.com