


Field Modification Kits

Pilot Devices

• Revised •
07/20/15

Selection

Push Buttons and Selector Switches	Class	Enclosure Type	Controller Size or (Lighting Rating)	Type	Catalog Number	List Price \$		
 49SBPB5  49SBSB1  49SAP05  49SAS01	14, 40, LC, LEN, CLM [Ⓛ]	Open	00-4	Start, Stop Push Buttons	49SAPB5			
		1	00-4 or (20–100A)	Hand-Off-Auto Selector Switch	49SASB1			
				Off-On Selector Switch	49SASB4			
				Start, Stop Push Buttons	49SBPB5			
				Hand-Off-Auto Selector Switch	49SBSB1			
			5-8 or (200–400A)	Off-On Selector Switch	49SBSB4			
				Start, Stop Push Buttons	49SAP05			
				Hand-Off-Auto Selector Switch	49SAS01			
				Keyed Hand-Off-Auto (key removable in all positions)	49SAS09			
		12, 4/4X	00-8 or (20–400A)	Off-On Selector Switch	49SAS04			
				Start, Stop Push Buttons	49SAP05			
				Hand-Off-Auto Selector Switch	49SAS01			
Keyed Hand-Off-Auto (key removable in all positions)	49SAS09							
22, 43	Open	00-4	Forward-Off-Reverse Selector Switch	49SASB2				
	1	00-4	Forward-Off-Reverse Selector Switch	49SBSB2				
		5-8	Forward, Reverse, Stop Push Buttons	49SAP02				
		Forward-Off-Reverse Selector Switch	49SAS02					
		12, 4/4X	0-8	Forward, Reverse, Stop Push Buttons	49SAP02			
	Forward-Off-Reverse Selector Switch			49SAS02				
	30 (2S1W)			Open	0-4	High-Off-Low Selector Switch	49SASB3	
				1	0-1 ¾	High-Off-Low Selector Switch	49SBSB3	
2-4		High, Low, Stop Push Buttons	49SAP03					
High-Off-Low Selector Switch		49SAS03						
12, 4/4X		0-4	High, Low, Stop Push Buttons		49SAP03			
			High-Off-Low Selector Switch	49SAS03				
			30 (2S2W)	Open	0-4	High-Off-Low Selector Switch	49SASB3	
				1	0-4	High-Off-Low Selector Switch	49SBSB3	
12, 4/4X	0-4	High, Low, Stop Push Buttons		49SAP03				
		High-Off-Low Selector Switch		49SAS03				
		1, 12, 4/4X		0-8 (20-400A)	Start, Stop Push Buttons	49SAP05		
					Hand-Off-Auto Selector Switch	49SAS01		
Keyed Hand-Off-Auto (key removable in all positions)	49SAS09							
Off-On Selector Switch	49SAS04							
25, 26	1, 12, 4/4X	0-8	Forward, Reverse, Stop Push Buttons	49SAP02				
			Forward-Off-Reverse Selector Switch	49SAS02				
32	1, 12, 4/4X	0-4	High, Low, Stop Push Buttons	49SAP03				

① To be used for replacement of switch only. Does not include relay or extra contact block on 30-400A CLM and CM Lighting Contactors. Class 49SB not available for these devices.

Description	Class	Enclosure Type	Controller Size or (Lighting Rating)	Lens Color(s)	Legend(s)	Voltage	Catalog Number	List Price \$
 49SBLBF	14, 40, 22 ^② , 43 ^② , 30 (2S2W) ^③ , LC, LEN, CLM	1	00–4 or (20–200A)	Red, Green, Amber	ON, RUN, OFF ^④ , OL TRIPPED ^⑤ , FORWARD, REVERSE, LOW, HIGH	24 Vac 120 Vac 208/240/277 Vac 480 Vac 600 Vac	49SBLBJ 49SBLBF 49SBLBG 49SBLBH 49SBLBE	
		1 12, 4/4X	5–8 or (300–400A) 0–8 or (20–400A)	Red (Transformer Type)	ON	24 Vac (Full Voltage) 120 Vac 240 Vac 480 Vac 600 Vac	49SPL0BRJ 49SPL0BRF 49SPL0BRG 49SPL0BRH 49SPL0BRE	
						24 Vac (Full Voltage) 120 Vac 240 Vac 480 Vac 600 Vac	49SPL0AGJ 49SPL0AGF 49SPL0AGG 49SPL0AGH 49SPL0AGE	
				Green (Transformer Type)	OFF ^④	24 Vac (Full Voltage) 120 Vac 240 Vac 480 Vac 600 Vac	49SPL0BRJ 49SBLBF 49SBLBG 49SBLBH 49SBLBE	
						24 Vac (Full Voltage) 120 Vac 240 Vac 480 Vac 600 Vac	49SPL0BRJ 49SPL0BRF 49SPL0BRG 49SPL0BRH 49SPL0BRE	
						24 Vac (Full Voltage) 120 Vac 240 Vac 480 Vac 600 Vac	49SPL0AGJ 49SPL0AGF 49SPL0AGG 49SPL0AGH 49SPL0AGE	
				Red (Transformer Type)	ON	24 Vac (Full Voltage) 120 Vac 240 Vac 480 Vac 600 Vac	49SPL0BRJ 49SPL0BRF 49SPL0BRG 49SPL0BRH 49SPL0BRE	
						24 Vac (Full Voltage) 120 Vac 240 Vac 480 Vac 600 Vac	49SPL0AGJ 49SPL0AGF 49SPL0AGG 49SPL0AGH 49SPL0AGE	
						24 Vac (Full Voltage) 120 Vac 240 Vac 480 Vac 600 Vac	49SPL0BRJ 49SPL0BRF 49SPL0BRG 49SPL0BRH 49SPL0BRE	
						24 Vac (Full Voltage) 120 Vac 240 Vac 480 Vac 600 Vac	49SPL0AGJ 49SPL0AGF 49SPL0AGG 49SPL0AGH 49SPL0AGE	
				Green (Transformer Type)	OFF ^④	24 Vac (Full Voltage) 120 Vac 240 Vac 480 Vac 600 Vac	49SPL0BRJ 49SPL0BRF 49SPL0BRG 49SPL0BRH 49SPL0BRE	
						24 Vac (Full Voltage) 120 Vac 240 Vac 480 Vac 600 Vac	49SPL0AGJ 49SPL0AGF 49SPL0AGG 49SPL0AGH 49SPL0AGE	
 49SPL0BRF	30 (2S1W) ^②	1	0–4	Red, Green, Amber	ON, RUN, OFF ^④ , OL TRIPPED ^⑤ , FORWARD, REVERSE, LOW, HIGH	24 Vac 120 Vac 208/240/277 Vac 480 Vac 600 Vac	49SBLBJ 49SBLBF 49SBLBG 49SBLBH 49SBLBE	
		1	2–4	Red (Transformer Type)	ON	24 Vac (Full Voltage) 120 Vac 240 Vac 480 Vac 600 Vac	49SPL0BRJ 49SPL0BRF 49SPL0BRG 49SPL0BRH 49SPL0BRE	
						24 Vac (Full Voltage) 120 Vac 240 Vac 480 Vac 600 Vac	49SPL0AGJ 49SPL0AGF 49SPL0AGG 49SPL0AGH 49SPL0AGE	
						24 Vac (Full Voltage) 120 Vac 240 Vac 480 Vac 600 Vac	49SPL0BRJ 49SPL0BRF 49SPL0BRG 49SPL0BRH 49SPL0BRE	
						24 Vac (Full Voltage) 120 Vac 240 Vac 480 Vac 600 Vac	49SPL0AGJ 49SPL0AGF 49SPL0AGG 49SPL0AGH 49SPL0AGE	
				Green (Transformer Type)	OFF ^④	24 Vac (Full Voltage) 120 Vac 240 Vac 480 Vac 600 Vac	49SPL0BRJ 49SPL0BRF 49SPL0BRG 49SPL0BRH 49SPL0BRE	
						24 Vac (Full Voltage) 120 Vac 240 Vac 480 Vac 600 Vac	49SPL0AGJ 49SPL0AGF 49SPL0AGG 49SPL0AGH 49SPL0AGE	
						24 Vac (Full Voltage) 120 Vac 240 Vac 480 Vac 600 Vac	49SPL0BRJ 49SPL0BRF 49SPL0BRG 49SPL0BRH 49SPL0BRE	
						24 Vac (Full Voltage) 120 Vac 240 Vac 480 Vac 600 Vac	49SPL0AGJ 49SPL0AGF 49SPL0AGG 49SPL0AGH 49SPL0AGE	
				Red (Transformer Type)	ON	24 Vac (Full Voltage) 120 Vac 240 Vac 480 Vac 600 Vac	49SPL0BRJ 49SPL0BRF 49SPL0BRG 49SPL0BRH 49SPL0BRE	
						24 Vac (Full Voltage) 120 Vac 240 Vac 480 Vac 600 Vac	49SPL0AGJ 49SPL0AGF 49SPL0AGG 49SPL0AGH 49SPL0AGE	
						24 Vac (Full Voltage) 120 Vac 240 Vac 480 Vac 600 Vac	49SPL0BRJ 49SPL0BRF 49SPL0BRG 49SPL0BRH 49SPL0BRE	
 49SBLBL	Lens Kit ONLY (30 (2S1W)) (14, 40, 22, 43, 30 (2S2W), LC, LEN, CLM)	1	0–1 ¾ 00–4 or (20–200A)	Red, Green, Amber	—	—	49SBLBL	
		—	—	Red	—	24 V AC/DC	52AED2	
				Green			52AED3	
				Amber			52AED4	
				White			52AEDB	
				Red		120 - 600 V AC/DC	52AEB2	
				Green			52AEB3	
				Amber			52AEB4	
				White			52AEBB	
				—				
				—				
				—				

① “Off” PL requires: (1) N.C. aux contact, 49AB01 on sizes 00–4.
② Class 22, 25, 26, 30, 32, 43, 83 & 84 requires qty. of (2) pilot light kits. Does not apply to 49SB kits. Select appropriate legend plate as a separate item per

type of starter; either “FORWARD” & “REVERSE” or “LOW” & “HIGH”.
③ 2S2W is starter size 0–4.
④ Includes NC aux contact for NEMA starter Size 0–4.

⑤ The “OL TRIPPED” pilot light with a bimetal OLR, requires the OLR to have a N.O. contact as well as a N.C. contact.
⑥ LED bulb applies to only 49SP* pilot lights. They do not apply to 49SB* pilot lights.