

# Visual 350 Fault Locator

CORNING

Corning VFL-350 visual fault locator is a compact pen design fault locator used to check single-mode and multimode optical fiber cables and components for faults or to locate individual fibers in a bundle. By transmitting a bright beam of red light into a fiber, breaks or improper terminations can be seen as a glowing red light. This device fits all 2.5 mm connector ferrules and is ideal for field installation of UniCam® MT-RJ and LC connectors containing the continuity test set (CTS) feature. There is an optional 1.25 mm adapter for the LC connectors. The VFL-350 operates on two AAA batteries and emits laser light of 635 nm (LASER Class 2 in accordance with IEC 825-2) with an output power less than 1mW. The robust and compact metal housing makes the device suitable for daily on-site use.



Part Number: VFL-350



Part Number: VFL-350

CORNING

# Visual 350 Fault Locator



## Specifications

### General Specifications

Technology	No-Epoxy/No-Polish
Product Type	Connector Tools and Tool Kits

### Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2002/95/EG
------	---

## Ordering Information

Part Number	VFL-350
Product Description	Visual Fault Locator, 635 nm penlight style
EAN Code	4056418200378

## Shipping Information

Units per Delivery	1/1
Weight	0.112 kg (0.24 lb)



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • [www.corning.com/opcomm](http://www.corning.com/opcomm)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/trademarks](http://www.corning.com/opcomm/trademarks). All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2016 Corning Optical Communications. All rights reserved.

