

NEC MultiSync® EA Series

Business Desktops 22" | 23" | 24" | 27" | 29" | 30"
UHD Desktops 24" | 27"



High-performance, LED-backlit LCD
displays ideal for corporate environments

Reimagine your desktop computing experience.

With its 4th & 5th generation MultiSync EA Series, NEC has developed monitor solutions that push the boundaries of what you've come to know as business-class screen performance. The EA Series deliver a completely redesigned chassis with a host of enhanced features, advanced technologies, future-proof connectivity and environmentally friendly benefits. All models utilize IPS LCD panels, which boast the best possible color accuracy and minimal viewing angle shift.

These models also feature LED backlights, which not only reduces power by up to 52% compared to their predecessors, but leads to a 30% thinner and 25% lighter chassis. Other green features include ECO Mode™, a carbon footprint meter and an ambient light sensor, which automatically adjusts the brightness to the optimal setting depending on ambient lighting, screen content or both, conserving power up to 87% compared to typical energy consumption. In addition, the human sensor detects user activity in front of the monitor and reduces display power up to 95% with inactivity.

The ground breaking ControlSync™ technology allows users to control up to six select MultiSync EA Series units in a multi-monitor configuration. Upon establishing one unit as the master, you will be able to simultaneously control many performance attributes of the multi-monitor setup through the master monitor.

| EA Series Desktops | |
|--------------------|----------|
| 22" | EA224WMI |
| 23" | EA234WMI |
| 24" | EA244WMI |
| 24" | EA244UHD |
| 27" | EA275UHD |
| 27" | EA274WMI |
| 29" | EA294WMI |
| 30" | EA304WMI |



Highlights

- LED backlight technology provides for industry-leading low power consumption and less hazardous materials
- Four-way ergonomic stand boasts pivot, tilt, swivel and height adjustment up to 130mm to maximize your viewing comfort
- Touch-sensitive OSD® controls are integrated into the bezel, making display adjustments easier than ever
- Integrated USB hub easily connects you to your peripherals
- Comprehensive input panel, including DisplayPort, HDMI, DVI-D and 15-pin VGA *select models, connects you to the latest peripherals and future-proofs your investment
- Space saving, multimedia speakers, which enhance your computing experience, are hidden to maintain the monitor's aesthetic appeal (headphone jack also included)
- ControlSync enables multi-monitor setups of up to six monitors and controls up to 26 settings
- Customize Setting allows both users and IT administrators to set and restore preferred settings with just one touch, contributing to a free-seating business environment
- Smart sensing technology includes ambient light and human sensors, which considerably reduce power consumption by automatically detecting your work conditions and adjusting to the proper display brightness or entering Power Saving Mode
- Carbon footprint meter helps track and calculate the reduction of green gas emissions, while the resettable cost meter (via On Screen Display) indicates electricity cost savings based on currency settings
- NaViSet™ software offers an intuitive graphical interface, allowing for easy adjustment of display settings via mouse and keyboard. NaViSet Administrator provides all the advanced control to remotely located IT professionals.
- EPEAT Gold compliance ensures the displays reduce hazardous waste and electricity usage, resulting in lower energy costs and increased protection for the environment
- ENERGY STAR® compliance reduces electrical costs and lowers total cost of ownership

Specifications

| | EA224WMI | EA234WMI | EA244WMI | EA274WMI | EA294WMI | EA304WMI | EA244UHD | EA275UHD |
|----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------|----------------------------------------------------------|---------------------------------------------------------------|-----------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------|---------------------------------------------------------------|
| DISPLAY | | | | | | | | |
| Panel Technology | IPS | IPS | IPS | AH-IPS | IPS | AH-IPS | AH-IPS | AH-IPS |
| Backlight Type | W-LED | | | | | GB-R LED | | |
| Viewable Image Size | 21.5" | 23" | 24" | 27" | 29" | 29.8" | 23.8" | 27" |
| Aspect Ratio | 16:9 | 16:9 | 16:10 | 16:9 | 21:9 | 16:10 | 16:9 | 16:9 |
| Native Resolution | 1920 x 1080 | 1920 x 1080 | 1920 x 1200 | 2560 x 1440 | 2560 x 1080 | 2560 x 1600 | 3840 x 2160 | 3840 x 2160 |
| Pixel Pitch | 0.248mm | 0.267m | 0.27mm | 0.233mm | 0.262mm | 0.25mm | 0.14mm | 0.155mm |
| Pixels Per Inch (at native resolution) | 102 @ native resolution | 96 @ native resolution | 94 @ native resolution | 109 @ native resolution | 97 @ native resolution | 101 @ native resolution | 185 @ native resolution | 163 @ native resolution |
| Brightness (typical) | 250 cd/m² | 250 cd/m² | 350 cd/m² | 350 cd/m² | 300 cd/m² | 350 cd/m² | 350 cd/m² | 350 cd/m² |
| Contrast Ratio (typical) | 1000:1 (25,000: dynamic) | | | | | | | |
| Viewing Angle (typical) | 178° Vert., 178° Hor. (89U/89D/89L/89R) @ CR>10 | | | | | | | |
| Response Time (typical) | 6ms (with overdrive) | 6ms | 5ms | 6ms | | | | |
| Displayable Colors | More than 16.7 million | | | | | | | |
| Synchronization Range | | | | | | | | |
| Horizontal (Analog/Digital) | 31.5-83 kHz | 31.5-83 kHz | 31.5-77 kHz | 31.5-83 kHz | 31.5-83 kHz | 31.5-98.7kHz | 31.5-134 kHz | 31.5-134 kHz |
| Vertical | 56-75 Hz | | 56-60 Hz | 56-75 Hz | | 50-85 Hz | 30-75 Hz | 30-75 Hz |
| Input Signal | | | | | | | | |
| Video | Analog RGB 0.7 Vp-p/75 Ohms | | | | | | | |
| Sync | Separate Sync: TTL Level (Positive/Negative); Composite Sync: TTL Level (Positive/Negative); Composite Sync on Green: (0.3Vp-p negative 0.7Vp-p positive) | | | | | | | |
| Input Connectors | DisplayPort, HDMI, DVI-D, VGA 15-pin D-sub | | | | VGA 15-pin D-Sub (2), DVI-D (2), DisplayPort, HDMI / MHL | DisplayPort, HDMI, VGA, DVI-D | DVI-D(2), HDMI(2), DisplayPort(2) | DVI-D, HDMI, DisplayPort |
| POWER CONSUMPTION | | | | | | | | |
| On (typical) | 26W | 27W | 29W | 57W | 50W | 63W | 79W | 71W |
| Power Savings Mode (typical) | 0.43W | 0.41W | 0.47W | 0.8W | | 0.7W | 0.33W | 0.5W |
| PHYSICAL SPECIFICATIONS | | | | | | | | |
| Dimensions (WxHxD) | | | | | | | | |
| Net (with stand) | 20 x 14.6-19.7 x 8.6 in. / 507.4 x 370.2-500.2 x 218mm | 21.4 x 15.0-20.1 x 8.7 in. / 543.8 x 380.4-510.4 x 218mm | 21.9 x 16.1-21.2 x 9.1 in. / 556.2 x 408.9-538.9 x 230mm | 25.2 x 16.5 - 21.6 x 9.1 in. / 639.2 x 417.9 - 537.9 x 230 mm | 27.8 x 16.2-21.3 x 9.1 in. / 705.8 x 410.4- 540.4 x 230mm | 27.0 x 18.6 - 23.7 x 9.1 in. / 686.9 x 472.8 - 602.8 x 230.0 mm | 22.0 x 15.2 - 20.3 x 8.6 in. / 558.2 x 386.7 - 516.7 x 218.0 mm | 25.2 x 16.5 - 21.6 x 9.1 in. / 639.2 x 417.9 - 537.9 x 230 mm |
| Net (without stand) | 20 x 11.9 x 2.4 in. / 507.4 x 301.1 x 60.5mm | 21.4 x 12.7 x 2.4 in. / 543.8 x 321.6 x 60.5mm | 21.9 x 14.2 x 2.5 in. / 556.2 x 359.6 x 63.8mm | 25.2 x 14.9 x 2.6 in. / 639.3 x 377.8 x 66.5 mm | 27.8 x 12.7 x 2.7 in. / 705.8 x 321.8 x 69.1mm | 27.0 x 17.6 x 3.0 in. / 686.9 x 446.6 x 75.1 mm | 22.0 x 13.2 x 2.8 in. / 558.2 x 334.3 x 72.0 mm | 25.2 x 14.9 x 2.6 in. / 639.2 x 377.8 x 66.5 mm |
| Weight | | | | | | | | |
| Net (with stand) | 13.2 lbs. / 6 kg | 14.1 lbs. / 6.4 kg | 16.8 lbs. / 7 kg | 19.2 lbs / 8.7 kg | 21.2 lbs. / 9.6 kg | 24.3 lbs. / 11.0 kg | 16.3 lbs. / 7.4 kg | 20.1 lbs / 9.1 kg |
| Net (without stand) | 8.2 lbs. / 3.7 kg | 8.8 lbs. / 4.0 kg | 10.6 lbs. / 4.8 kg | 12.8 lbs. / 5.8 kg | 14.6 lbs. / 6.6 kg | 17.6 lbs. / 8.0 kg | 11.0 lbs. / 5.0 kg | 13.7 lbs. / 6.2 kg |
| VESA Hole Configuration | 100 x 100mm | | | | | | | |
| ENVIRONMENTAL CONDITIONS | | | | | | | | |
| Operating Temperature | 41-95°F / 5-35°C | | | | | | | |
| Operating Humidity | 20 - 80% | | | | | | | |
| Operating Altitude | 6562 ft. / 2000m | | 6562 ft. / 2000m | | 10,000 ft. / 3048m | 6562 ft. / 2000m | 6562 ft. / 2000m | 6562 ft. / 2000m |
| Storage Temperature | 14-140°F / -10-60°C | | | | | | | |
| Storage Humidity | 10-85% | | | | | | | |
| Storage Altitude | 40,000 ft. / 12,192m | | | | | | | |
| Tropical Environments | Yes | | | | | | | |
| ENVIRONMENTAL COMPLIANCE | | | | | | | | |
| ENERGY STAR | 6.0 | | | | | | | |
| TCO | 5.2 | Edge 1.2 | 6.0 | | 5.0 | 6.0 / Edge Certified 1.2 | Edge Certified 1.2 | Edge Certified 1.2 |
| EPEAT | Gold | | | | | | | |
| RoHS | Yes | | | | | | | |
| LIMITED WARRANTY | 3 years parts and labor, including backlight* | | | | | | | |
| ADDITIONAL FEATURES | Tilt; Swivel; Pivot; Height-adjustable stand; ControlSync; Customize Setting; Integrated speakers; 4-port USB hub; LED backlight; Auto brightness with ambient light sensor; Human sensor; ECO Mode; Carbon footprint meter; Resettable cost meter; Thin frame; Carrying handle; Rapid Response; Ambix; XtraView; Hot Key; Touch OSD controls; OSD Lock Out; Cable management; Dynamic Visual Mode (Standard, Text, Movie, Gaming, Photo, Dynamic); NaViSet Administrator 2; VESA mount; HDCP; DDC/CI; No Touch Auto Adjust; Plug and Play (VESA DDC2B); VESA DPMS power management; AccuColor color control; Digital smoothing; Digital controls; ISO 9241-307 Class I; DICOM SIM for IPS models | | | | | | | |
| SHIPS WITH | Setup sheet; User manual; Power cord; 15-pin D-sub cable; DVI-D cable; USB cable; Audio cable; ControlSync cable | | | | | Setup sheet; User manual; Power cord; DisplayPort cable; DVI-D cable; USB cable; Audio cable; ControlSync cable | Setup sheet; User manual; Power cord; DisplayPort cable; USB cable; Audio cable; ControlSync cable | |

* Warranty restrictions apply. Contact your representative for details.

Touch-sensitive OSD controls



Comprehensive input panel (select models)



USB 3.0 hub (select models)



4-way adjustable stand



Thin, lightweight design with integrated speakers



Ambient and human sensors



NEC MultiSync® EA Series



MultiSync is a registered trademark and ECO Mode and ControlSync are Trademarks of NEC Display Solutions. All other brand or product names are trademarks or registered trademarks of their respective holders. Product specifications subject to change.

©2015 NEC Display Solutions of America, Inc. and the NEC logo are registered trademarks of NEC.

NEC Display Solutions

500 Park Boulevard, Suite 1100
Itasca, IL 60143
866-NEC-MORE