



40 AMP HOUR 16X14X8 UPS BATTERY BACKUP



The AccelTex Solutions UPS Battery Backup Solutions are designed to provide backup power in the event of a main line power failure or for other periods of intentional or unintentional interrupted power events. These backup solutions are fully configured and provide multiple output power options, such as PoE and DC power and are Solar-Ready.

Part Number: ATS-UPS-40AH-16148P



FEATURES

- Fully integrated unit includes charge controller, batteries, enclosure and PoE injector
- Multiple output power options, including PoE (802.3af 802.3at) & 12V DC
- Multiple PoE outputs with an additional PoE Switch for powering multiple PoE devices, such as security cameras
- Batteries are continuously charged via PoE
- Charge controller protects against over-charging and over discharging of the batteries
- Enclosure ships with a Wall mount (Pole Mount is available as an accessory item)
- Outdoor-Rated



BENEFITS

- Self-Contained Unit for easy install
- Provides isolated and uninterrupted power
- Space for mounting electronics (on some models)



ADDITIONAL COMPATIBLE ACCESSORY ITEMS

- PoE Switch (ATS-POES-12VDC-56VDC)
- Enclosure Pole Mount (ATS-PMK-14)



APPLICATIONS

- Security Cameras
- Outdoor Wi-Fi
- Parking Lots and Garages
- Cellular Backhaul
- Remote Monitoring and Control

40 AMP HOUR 16X14X8 UPS BATTERY BACKUP

Part Number: ATS-UPS-40AH-16148P



MECHANICAL SPECIFICATIONS

Enclosure Weight: 39.1 lbs (17.74 kg)
Enclosure Dimensions: 16" H x 14" W x 8" D (406.4 mm H x 355.6 mm W x 203.2 mm D)
Color: Light Grey
Material: Polycarbonate
Door Type: Solid
Lock Type: Latch with Padlockable Hasp
Enclosure Installation: Mounting Feet



ELECTRICAL SPECIFICATIONS

System Output Power Options: 1 Output for 802.3af or 802.3at and 1 Output for 12V DC (Supports up to 10 Amps)
Charge Controller Max Input: 10 Amps



ENVIRONMENTAL SPECIFICATIONS

Installation Environment: Indoor or Outdoor (NEMA 6P, 4X, 4, 3R, 122; IP68)
Operating Temperature: -4 to 122°F (-20 to 50°C)



SYSTEM COMPONENTS

- (1) 12V 40 Ah AGM Sealed Lead Acid Battery
- 16x14x8 Polycarbonate Enclosure with Solid Door, Latch Locks, Pad Lockable Hasp and Wall Mount
- Battery Tray
- Charge Controller (802.3af/at PoE and 12V DC, 10 Amp Output Power)
- 50W PoE Injector for Charging Batteries and Data Connectivity
- (1) 15 cm and (1) 30 cm DIN Rail, (3) DIN Rail Mounts, (2) Universal DIN Rail Mounting Plates for equipment that is not DIN Rail Mount Ready and fasteners for equipment mounting
- (6) Battery Wiring Harnesses; (2) to controller and (4) to link batteries
- (1) PG16 and (1) PG7 Cord Grip
- (1) 85 cm Battery Safety Strap
- (1) Cable Management Supplies Kit (includes Zip Ties and Zip Tie Mounting Pads)

40 AMP HOUR 16X14X8 UPS BATTERY BACKUP

Part Number: ATS-UPS-40AH-16148P



RECOMMENDED SYTSTEM USAGE SCENARIOS

Watts Consumed	Total Hours of Backup*	Total Hours of Backup in Cold Environments**
2	240	168
4	120	84
6	80	56
8	60	42
10	48	34
12	40	28
14	34	24
16	30	21
18	27	19
20	24	17
22	22	15
24	20	14
26	18	13
28	17	12

* Calculations based on battery operation at room temperature. For cold environments, battery capacity is reduced by 25-30%.

** Battery capacity has been reduced by 30%.