



Universal Alarm Communicator

For Primary or Redundant Alarm Communications

The Uplink CDMAEZ includes the latest technology for the best performance and longest life cycle. Compatible with CDMA cellular networks, the CDMAEZ is designed as a summary event communicator.

The Uplink CDMAEZ communicates to central stations by dialup to any industry standard receiver, or over the internet to an IP receiver — all with the exceptional service and features you've come to expect from Uplink, the leading supplier of wireless security solutions.

Uplink Advantages

Secure dealer website for activation, configuration, and management

Flat-rate billing with no overage charges

Programmable periodic test intervals

Works with virtually any central station

Uplink Remote for interactive control and end-user notifications

Mobile activation and signal strength with Uplink Installer™

Live technical and activation support*

CDMAEZ Device Features:

- ✓ Universal cellular communications, for summary event reporting
- ✓ Power from the panel or separate 12V DC power supply
- ✓ Two web configurable outputs
- ✓ Installs in minutes with complete end-to-end signal verification
- ✓ Smart siren bell sampling to detect burglary or fire condition
- ✓ Web and smartphone apps for remote arming and disarming

*8:00 a.m. to 8:00 p.m. EST, Monday through Friday
Specifications subject to change without notice.

(888) 9-UPLINK | (888) 987-5465 | www.uplink.com | sales@uplink.com

A **Numerex** Solution



CDMAEZ Universal Alarm Communicator



A Trusted Partner

Uplink, a Numerex Solution, is the security industry's most trusted source for wireless alarm communicators.

Uplink delivers the unique combination of technology, quality, options, and superior value that have made us the industry's trusted source for security solutions since 1996.

With hundreds of thousands of installed devices throughout the United States, Mexico, and Canada, Uplink has the experience and expertise to provide reliable, award winning products with first class support.

Uplink technology is certified by the ISO/IEC27001 information security management standard and backed by a web-based dealer support management tool.

For more information, visit the Uplink website at uplink.com.

Technical Specifications

INPUTS	
Four Inputs	<ul style="list-style-type: none">• Input 1: Connect to siren/bell (distinguishes between burg/steady and fire/pulsed) or programmable to 12 volts• Inputs 2-4: 12 volts
OUTPUTS AND REPORTING	
Central Station	<ul style="list-style-type: none">• Contact ID, SIA, Pulse 4/2 (:20 PPS) and modem IIe/IIla²• Internet or dial-up
Relay Outputs	Two-configurable
Other Reporting	<ul style="list-style-type: none">• Low voltage• Email alerts to customer or alarm company
Testing	<ul style="list-style-type: none">• Weekly or daily
Status LEDs	<ul style="list-style-type: none">• Signal strength• Network• Service• Communications
POWER SOURCE – NOT INCLUDED	
Power Requirements	<ul style="list-style-type: none">• 12V DC• 500 mA max on transmit• 28mA standby
RADIO	
CDMA	Compatible with CDMA networks
Cellular Frequencies	850/1900 MHz
Transmit Power	Maximum allowable: <ul style="list-style-type: none">• 1.0W at 1900 MHz• 2.0W at 850 MHz
OPTIONAL ACCESSORIES	
Magnet mount antenna with 9ft cable - part number 1004ANT 8 inches tall high gain antenna with articulating joint - part number 1005ANT	
DIMENSIONS	
Height/Width/Depth (inches)	4.75/3.3/1.3
Antenna	3.75 inches

Specifications subject to change without notice.

(888) 9-UPLINK | (888) 987-5465 | www.uplink.com | sales@uplink.com

A **Numerex** Solution

