

SPECIFICATION SHEET 34-875

MAXIFLEX[®] SEAMLESS KNITS FOR GENERAL DUTY BY ATG[®]

- Ultra cool and very comfortable to wear, breathable coating keeps hands cool and dry
- Excellent dexterity, sensitivity and tactility
- Designed to produce minimal lint and dust;
- Minimal penetration (strike through) keeps the liner soft on the inside of the glove
- Silicone Free
- CFIA Approved
- Made from component material which comply with Federal regulations for food contact, 21CFR, 170-199
- This style is also available tri-folded and shrink-wrapped for carefree dispensing through vending machines (34-875V)

APPLICATIONS

- General Assembly
- Micro-engineering
- Automotive components
- Painting
- Horticulture

CARE INSTRUCTIONS

Recommend washing gloves in tempered water not exceeding 104°F or 40°C. A mild commercial laundry soap or detergent should be used. Wash in a 5-10 minute cycle time. Rinse in cold water. Tumble dry at temperature not exceeding 104° F or 40° C.

TECHNICAL DATA

| MATERIAL | Nylon liner with micro-foam nitrile coating | | | | | |
|------------|----------------------------------------------|--------------------|--------------------|--------------------|--------------------|--------------------|
| COLOR | 🔳 Grey with 🔳 Black | | | | | |
| CUFF STYLE | Continuous Knit | | | | | |
| SIZES | XXS - XL | | | | | |
| PACKAGING | 12 per dozen, 12 dozen per case | | | | | |
| CASE | 19.7" x 11.6" x 10.6" / 50cm x 29.5cm x 27cm | | | | | |
| CASE | XXS | XS | S | М | L | XL |
| WEIGHT | 11.2 lbs 5.1 kg | 11.9 lbs 5.4 kg | 13.2 lbs 6.0 kg | 15.0 lbs 6.8 kg | 15.7 lbs 7.1 kg | 16.3 lbs 7.4 kg |
| C00 | Sri Lanka | | | | | |

PERFORMANCE PROPERTIES

| ABRASION | 0 | 1 | 2 | 3 | 4 | 5 |
|----------|---|---|---|---|---|---|
| CUT | 0 | 1 | 2 | 3 | 4 | 5 |
| TEAR | 0 | 1 | 2 | 3 | 4 | 5 |
| PUNCTURE | 0 | 1 | 2 | 3 | 4 | 5 |

BARCODES


| ITEM | BAG | DOZEN | CASE |
|------------------|-----|----------------|----------------|
| 34-875/XL | | 01616314018039 | 02616314018039 |
| 34-875/L | | 01616314018022 | 02616314018022 |
| 34-875/M | | 01616314018015 | 02616314018015 |
| 34-875/ S | | 01616314018008 | 02616314018008 |
| 34-875/XS | | 01616314017995 | 02616314017995 |
| 34-875/XXS | | 01616314020339 | 02616314020339 |





DIMENSIONS (in/cm)

| | XXS | XS | S | М | L | XL |
|---|------------|------------|------------|------------|------------|------------|
| Α | 7.7 / 18.5 | 7.7 / 19.5 | 8.1 / 20.5 | 8.7 / 22.0 | 8.9 / 22.5 | 9.1 / 23.0 |
| В | 3.0 / 7.5 | 3.2 / 8.2 | 3.5/ 8.8 | 3.5 / 9.0 | 3.9 / 9.8 | 4.0 / 10.2 |
| н | Purple | Blue | 🗆 White | Green | Brown | Yellow |



PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®

AMERICAS: (800) 262-5755 • (518) 861-0133 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | www.pipglobal.com

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED.