HellermannTyton



Article Number: 166-90220

HoloCuard SP DVC Tubing Smoot

HelaGuard SR PVC Tubing, Smooth Bore, Spiral Cover, Std Wt, 0.38" Dia, Bk, 100 ft/Std. Reel

Base Data		
	Local Order Number	166-90220
	Туре	PSR0380
	Color	
		Black (BK)
	Features and benefits	 Spiral reinforced construction provides protection from crushing yet remains extremely flexible. Lightweight, easy-to-use material reduces installation time and labor costs. Material stands up to vibration and limited torsional movement without creation of stress points or cracks. Smooth inside bore protects wires and eases insertion of wire bundles. UV resistant; suitable for use in outdoor applications.
	Quantity Per	reel
	Product Description	A lightweight tubing with a smooth inside bore, made of a spiral reinforced PVC material that provides high flexibility. This tubing is well-suited for protecting wire and cable bundles in extremely tight spaces. UV resistant. Use with HelaGuard Non-Metallic Compression Fittings to create an enclosed system.
	Short Description	HelaGuard SR PVC Tubing, Smooth Bore, Spiral Cover, Std Wt, 0.38" Dia, Bk, 100 ft/Std. Reel
Product Dimensions		
	Length L (Imperial)	100.0ft
	Length L (Metric)	30.5m
	Inner Diameter D (Imperial)	0.48"
	Inner Diameter ID (metric)	12mm
	Trade Size	3/8 "
	Outside Diameter D (imperial)	0.65"
	Outside Diameter OD (metric)	16.5mm
	Nominal Diameter (Imperial)	3/8"
	Nominal Diameter (Metric)	16mm
	Inside Bend Radius (Imperial)	0.99"
	Inside Bend Radius (Metric)	25mm

166-90220

HellermannTyton

Material and Specifications		
	Material	Polyvinylchloride (PVC)
	Material Shortcut	PVC
	Flammability	Self-Extinguishing according to EN IEC 61386
	Halogenfree	No
	Operating Temperature	-4°F to +158°F (-20°C to +70°C)
	ROHS Compliant	Yes
	UL Recognized (US)	Yes
	UL Recognized (US and Canada)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	100ft
	Package Quantity (Metric)	30.5m
	Customs Number(Schedule B)	3926909987