

553-50237

HellermannTyton

Article Number: 553-50237

Description: Heat Shrink Labels, 1.0" (25.4mm), Single Sided, PO-X, White, 1000/box



Base Data		
	Local Order Number	553-50237
	Type	HST24-8WH
	Color	White (WH)
	Features and benefits	<ul style="list-style-type: none"> • Slide Slit and optional center slits for easy wire insertion. • Smooth surface for clean and legible printing. • Supplied on a ladder style carrier so that markers can be kitted after printing. • A 3:1 shrink ratio means fewer skews as each marker covers a wider range of wire diameters.
	Quantity Per	pack
	Product Description	HellermannTyton's ShrinkTrak heat shrinkable markers make it easy to mark wire, cable and other components. The military approved heat shrink tubing is flattened and assembled in a ladder style carrier system for easy printing using a thermal transfer printer. The ladder system creates a kit of markers that can be sorted, removed and applied in any order thus saving time, labor and speeding production.
	Short Description	Heat Shrink Labels, 1.0" (25.4mm), Single Sided, PO-X, White, 1000/box
Product Dimensions		
	Length L (Imperial)	1.69"
	Length L (Metric)	42.9mm
	Printable (Yes/No)	Yes
	Variant	Thin-Wall
	Height H (Imperial)	1.69"
	Height H (Metric)	42.93mm
	Diameter Max. (Imperial)	1.0"
	Outside Diameter Max. (Imperial)	1.0"
	Outside Diameter Max. (Metric)	25.4mm
	Wall Thickness WT (Imperial)	0.039"
	Wall Thickness WT (Metric)	1.0mm
	Flexibility	Flexible
	Print Method	Thermal transfer

553-50237

HellermannTyton

Product Dimensions	Recovered Diameter d (metric)	8.4mm
	Recovered Diameter d (imperial)	0.33"
	Supplied Diameter D (metric)	26.0mm
	Supplied Diameter D (imperial)	1.024"
	Thickness T (Metric)	3.0µm
	Width of Liner WL (imperial)	3.0"
	Width of Liner WL (metric)	76.2mm
Material and Specifications		
	Material	Polyolefin, cross-linked (PO-X)
	Material Shortcut	PO-X
	US MILSPEC	SAE-AS81531
	Dielectric Strength (Metric)	19.7 kV min.
	Flammability	UL 224 VW-1
	Shrink Temperature	+194 °F (+90 °C)
	Operating Temperature	-67°F to +275°F (-55°C to +135°C)
	ROHS Compliant	Yes
	Certification/Specification	UL224 125 °C 600V VW-1
Logistic and Packaging		
	Package Quantity (Imperial)	1000
	Package Quantity (Metric)	1000