

596-00028



Article Number: 596-00028

Description: Thermal Transfer Labels, .63" x .31", 6 Across, Polyester, White, 1000/roll



Base Data		
	Local Order Number	TAGPP1T6-822
	Type	TAGPP1T6
	Color	White (WH)
	Features and benefits	<ul style="list-style-type: none"> • Thermal transfer labels are made with high performance materials for long term industrial applications. • Labels can be printed in any standard thermal transfer printer giving the user options for printing and eliminating the need to be dedicated to one printer model. • The labels are available in a wide variety of sizes so that finding a label for a particular application is easy.
	Quantity Per	reel
	Product Description	Labels are made with various high performance materials including polyester, metalized polyester, clear polyester, cloth, polyimide and the Durattach label stock. The construction includes an aggressive acrylic adhesive and abrasion and chemical resistant top coatings that are made to accept ink from a thermal transfer printer. The product is supplied on rolls on a 3" cardboard core.
	Short Description	Thermal Transfer Labels, .63" x .31", 6 Across, Polyester, White, 1000/roll
Product Dimensions		
	Length L (Imperial)	0.13"
	Length L (Metric)	7.92mm
	Width W (Imperial)	0.625"
	Width W (Metric)	15.87mm
	Height H (Imperial)	3.75"
	Height H (Metric)	95.25mm
	Height H2 (Imperial)	3.75"
	Height H2 (Metric)	95.25mm
	Bundle Diameter Min. (Imperial)	.39"
	Bundle Diameter Min. (Metric)	1.0mm
	Bundle Diameter Max. (Imperial)	.87"
	Bundle Diameter Max. (Metric)	22.20mm

596-00028



Product Dimensions	Horizontal Repeat HR (metric)	27.30mm
	Horizontal Repeat HR (imperial)	1.08"
	Print Method	Thermal transfer
	Vertical Repeat VR (imperial)	0.75"
	Vertical Repeat VR (metric)	19.05mm
	Width of Liner WL (imperial)	3.80"
	Width of Liner WL (metric)	96.52mm
Material and Specifications		
	Material	Type 822, Polyester, white (WH)
	Material Shortcut	822
	Adhesive	Acrylic
	Adhesive Operating Temperature	-40°F to +194°F (-40°C to +90°C)
	Halogenfree	Yes
	Operating Temperature	-40°F to +302°F (-40°C to +150°C)
	ROHS Compliant	Yes
	Certification/Specification	UL-Recognized
	UL Recognized (US)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	1000
	Package Quantity (Metric)	1000
	Customs Number(Schedule B)	3919102055
	Labels per Row	6