

Article Number: 596-00751

SOLAR SYSTEM BREAKER Description: Solar Label, SOLAR SYSTEM BREAKER, 2.0" x 1.0", VL,

Red, 50/roll

Base Data		
	Local Order Number	596-00751
	Туре	SSB
	Color	Red (RD)
	Features and benefits	 Made with UV stable inks and materials for durability and weather resistance. The labels are supplied with aggressive adhesive to ensure long life. Solar Installation labels meet NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.
	Quantity Per	roll
	Product Description	HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the 2014 National Electrical Code (NEC 2014) and the 2012 International Fire Code (IFC 2012) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.
	Technical Description	Pre-Printed Solar Label, 2" X 1", Solar System Breaker, Vinyl, Red, 50/RL
	Short Description	Solar Label, SOLAR SYSTEM BREAKER, 2.0" x 1.0", VL, Red, 50/roll
Product Dimensions		
	Width W (Imperial)	2.0"
	Width W (Metric)	50.8mm
	Height H (Imperial)	1.0"
	Height H (Metric)	25.40mm
Material and Specifications		
	Material	Vinyl
	Material Shortcut	V
	Adhesive	Acrylic
	Adhesive Operating Temperature	-40°F to +174°F (-40°C to +79°C)
	Halogenfree	Yes

generated on: 7/2/2017

596-00751



Material and Specifications	Operating Temperature	-40°F to +174°F (-40°C to +79°C)
	ROHS Compliant	Yes
	UL Recognized (US)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	50
	Package Quantity (Metric)	50
	Customs Number(Schedule B)	3919905060

generated on: 7/2/2017