HellermannTyton

Article Number: 596-00860

Description: MAIN PHOTOVOLTAIC SYSTEM DISCONNECT

Metal Solar Placard, 2017 Code, MAIN PV SYSTEM DISCONNECT, 5.5' x 1.75", AL, Red, 5/pkg

Base Data		
	Local Order Number	596-00860
	Туре	MPVSDM5
	Color	Red (RD)
	Features and benefits	 Placards made with UV stable inks and materials tested to last up to 25 years, even in direct sun exposure. Aggressive adhesive ensures strong bond, even on powder coated surfaces. Meets or exceeds NEC & IFC standards for printed text, character height, color and outdoor UV stability. Optional Paint Shields provide additional protection for pre-printed and variable data placards.
	Quantity Per	pack
	Product Description	Metal Solar Placards offer maximum durability for labeling photovoltaic equipment and components. A special printing process fuses UV stable inks to the placards for long-lasting results, tested to last up to 25 years—even in direct sunlight. Metal Solar Placards are designed to meet or exceed National Electrical Code (NEC) and the requirements of local Authorities Having Jurisdiction (AHJs), that may prefer a placard-style marking over thermal transfer printed labels.
	Technical Description	5.5" X 1.75" Black text on red background that reads as: "MAIN PV SYSTEM DISCONNECT." in 3/8" tall characters. 10 per pkg.
	Local Order Number 2	Cross Reference = Paint Shield: 596-00795
	Short Description	Metal Solar Placard, 2017 Code, MAIN PV SYSTEM DISCONNECT, 5.5' x 1.75", AL, Red, 5/pkg
Product Dimensions		
	Length L (Imperial)	5.5"
	Length L (Metric)	139.7mm
	Width W (Imperial)	5.5"
	Width W (Metric)	139.7mm
	Height H (Imperial)	1.75"
	Height H (Metric)	44.40mm
Material and Specifications		
	Material	Anodized Aluminum (AA)

596-00860

HellermannTyton

Material Shortcut	AA
Adhesive	Ultra High Bond Permanent Acrylic Adhesive
Adhesive Operating Temperature	from +50°F (from +10°C)
Halogenfree	Yes
Operating Temperature	-40°F to +203°F (-40°C to +95°C)
ROHS Compliant	Yes
Certification/Specification	NEC2014
UL Recognized (US)	Yes
Package Quantity (Imperial)	5
Package Quantity (Metric)	5
Customs Number(Schedule B)	7616995095
	Adhesive Adhesive Operating Temperature Halogenfree Operating Temperature ROHS Compliant Certification/Specification UL Recognized (US) Package Quantity (Imperial) Package Quantity (Metric)