



2 Megapixel IR PoE IP Dome

IV-DEF802MPW_IV-DEF802MPB

Features:

- . 1/2.8" Sony Exmor, 1080P
- . 0.1Lux @(F1.4,AGC ON), 0Lux with IR
- . H.264 high profile / JPEG Snapshot
- . Fixed lens 8.00 mm
- . IR-CUT filter switch
- . Dual stream, 3-Axis
- . Built in PoE, ONVIF 2.0
- . Color: White or Black
- . Junction Box included



Specification		IV-DEF802MPW_IV-DEF802MPB
Camera	Image Sensor	1/3" 2 Megapixel Sony Exmor
	Effective Pixels	1920 x 1080
	Scanning System	Progressive
	Min. Illumination	Color:0.1Lux / F1.4, B/W: 0.01 Lux / F1.4; 0 Lux (IR on)
	Electronic Shutter	Auto / Manual 1/50 ~ 1/10,000
	Day & Night	Auto (ICR) / Color / B/W
	S/N Ratio	> 50dB
	IR distance	105 feet
	Backlight Compensation	BLC
	White Balance	Auto
	Gain Control	Auto / Manual
	Noise Reduction	3D
	Privacy Masking	Up to 4 Areas
	Slow Shutter	None /Low/ Middle/ High
	Motion Detection	22X18 area
Lens	Focal Lens	8.0 mm / F2.0
	Mount Type	Board-in Type
Video	Compression	H.264 Main Profile, JPEG Snapshot
	Resolution	60Hz Mode:1080P(1920×1080) / 720P(1280x720) / D1(704X576) / CIF(352X288)
	Frame Rate	Main stream: 1920 x 1080 (1 ~ 30fps), sub stream: 704x576 (1 ~ 30fps)
	Bit Rate	H.264: 64K~8192 Kbps
Network	Ethernet	RJ-45 (10/100 Base-T)
	Protocols	IPv4, HTTP, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Cloud
	ONVIF	ONVIF Ver. 2.0
	Max. User Access	5 users
	Smart Phone	iPhone,Windows Mobile, BlackBerry,Symbian, Android
	Browser	IE、Chrome、Firefox、Safari
General	Operating Condition	14 °F ~ 122 °F (-10°C~50°C), Humidity10%~ 90%
	Power Supply	DC12V, PoE (802.3af)
	Power Consumption	<10W
	Protection Range	IP66
	Dimension	3.5" x 4.25"
	Weight	1.43 lbs