


UPLINK'S PRODUCTS DELIVER THE
UNIQUE COMBINATION OF RELIABLE
TECHNOLOGY AND SUPERIOR VALUE
THAT HAS MADE UPLINK THE SECURITY
INDUSTRY'S MOST TRUSTED SOURCE
FOR ALARM COMMUNICATORS




4G FOR FREE

We make it easy to upgrade from 2G to 4G!
Simply replace any of your 2G
communicators with new Uplink 4G and
CDMA communicators and qualify for
additional free units.


Accessories




1001ANT
• Gain (dBi peak): 3.5




1005ANT
• Gain (dBi peak): 3.5




1010ADP
• SMA to TNC
antenna adapter




4500CAB
• Cable for direct
connect to Elk Panels




1020CAB
• OBD Y-Cable for
Uplink GPS




1004ANT
• Gain (dBi peak): 3.5
• Cable length: 3 Meters
• Connector: Female SMA



20CAB
• 20' Antenna
Extension Cable



50CAB
• 50' Antenna
Extension Cable



**UPLINK 5300
WI-FI ADAPTER**
• Connects the Model
5200 to a Wi-Fi router
• Powered off the 5200

Product Specifications

MODEL	PRODUCT DESCRIPTION	DIMENSIONS H/W/D INCHES	WEIGHT
CDMA30	CDMA Primary alarm communicator	10.5 x 5.4 x 2.5/ antenna 3.75	2 LB
CDMA50	CDMA Backup alarm communicator	10.5 x 5.4 x 2.5/ antenna 3.75	2 LBS
4550CB	UL Listed 4G Communicator for Commercial Security	12.2 / 7.5 / 3.9 / 7.75 w/ antenna	7 LBS
4550CF	UL Listed 4G Communicator for Commercial Fire	12.2 / 7.5 / 3.9 / 7.75 w/ antenna	9 LBS
4500EZ	Universal 4G Communicator for Primary or Redundant	4.75 / 3.3 / 1.3	1 LB
4550	UL Listed 4G Backup Resi communicator	12.2 / 7.5 / 3.9 / 7.75 w/ antenna	2 LBS
4530EX	Low-cost Primary Communicator with full-data or summary reporting	10.5 / 5.4 / 2.5 / 3.75 w/ antenna	1 LBS
5200	Broadband Alarm Communicator	4.5 x 3 x 1	1 LB
5300	WI-FI Adapter	4 x 1.75 x .7	< .5 LB
1020AUTO	UplinkGPS auto plug-in tracking device	N/A	< .5 LB
1020PRO	UplinkGPSautoPRO Hard Wired tracking device	N/A	< .5 LB
1001ANT	Antenna – Standard	N/A	< .5 LB
1004ANT	Antenna Mag mount	N/A	< .5 LB
1005ANT	Antenna – high-gain	N/A	< .5 LB
1020CAB	Y Cable for GPSauto	N/A	< .5 LB
1010ADP	Cable Antenna adapter	N/A	< .5 LB
4500CAB	Cable for ELK	N/A	< .5 LB
20CAB	Cable 20ft	N/A	2.5 LB
50CAB	Cable 50ft	N/A	5 LB

(888) 9-UPLINK | (888) 987.5465 | www.uplink.com | sales@uplink.com

Powered by **Numerex**

Better Technology, More Options



© 2013 Uplink Security LLC. All rights reserved. Uplink is a trademark of Uplink Security LLC. UL and the UL Mark are trademarks of Underwriters Laboratories, Inc.

UL_0001_R4

uplink®

Better Technology,
More Options

4G Communicators

CDMA Communicators

Remote Services & Apps

GPS Tracking



Cellular Alarm Communicators

CDMA



UPLINK CDMA30

CDMA TECHNOLOGY IMMUNE FROM GSM UPGRADES

- Primary communicator for full event reporting
- Power from the panel or separate 12V DC power supply
- Dial capture for full event reporting by Contact ID, SIA, Pulse 4/2, or Model IIe/IIa/IIa², DMP
- Supports Uplink Remote (Requires 25XOREM Board)

CDMA



UPLINK CDMA50

CDMA TECHNOLOGY IMMUNE FROM GSM UPGRADES

- Telephone Line Monitoring for Backup, programmable for primary
- Dial capture for full event reporting by Contact ID, SIA, Pulse 4/2, or Model IIe/IIa/IIa², DMP
- Requires 16.5V AC - 45 VA transformer – not included
- Optional 12V battery – not included
- Supports Uplink Remote (Requires 25XOREM Board)

4G



UPLINK 4500EZ

PRIMARY OR REDUNDANT 4G COMMUNICATIONS

- Connect to bell output for burglary or fire signaling, three additional inputs plus two outputs
- Central station reporting by Contact ID, SIA, Pulse 4/2 or Modem IIe/IIa/IIa², DMP
- Power from the panel or separate 12V DC power supply
- Supports Uplink Remote

4G



UPLINK 4530EX

ECONOMICAL 4G COMMUNICATOR

- Dial-Capture for full-event reporting and Siren/Bell Sampling for summary-event reporting
- Dial capture for full event reporting by Contact ID, SIA, Pulse 4/2, or Modem IIe/IIa/IIa², DMP
- Override panels account and phone numbers for easier takeovers
- Supports Uplink Remote

4G



UPLINK 4550CB

UL LISTED 4G FOR BANK VAULT RATED MAXIMUM COMPLIANCE

- Dial capture for full event reporting by Contact ID, SIA, Pulse 4/2, or Modem IIe/IIa/IIa², DMP
- Backup 4G Communicator
- Low-profile, tamper-resistant enclosure
- Requires UL listed 16.5V AC - 45 VA transformer – not included
- Optional 12V battery – not included
- Supports Uplink Remote

4G



UPLINK 4550CF

UL LISTED 4G FOR COMMERCIAL FIRE BACKUP

- UL 864 listed. Complies with NFPA 72
- Dial capture for full event reporting by Contact ID, SIA, Pulse 4/2, or Modem IIe/IIa/IIa², DMP
- Requires UL listed 16.5V – 45 VA transformer – included
- Optional 12V battery – not included
- Supports Uplink Remote

4G



UPLINK 4550

4G WIRELESS ALARM COMMUNICATOR

- UL Listed for Household Burglary and Fire Alarm
- Telephone Line Monitoring for Backup, programmable for primary
- Dial capture for full event reporting by Contact ID, SIA, Pulse 4/2, or Modem IIe/IIa/IIa², DMP
- Requires UL listed 16.5V AC - 45 VA transformer – not included
- Optional 12V battery – not included
- Fast Easy Installation – No Programmer Required
- Supports Uplink Remote



UPLINK 5200

UNIVERSAL BROADBAND ALARM COMMUNICATOR

- Direct replacement of the telephone line using a hardwired connection to a standard router
- Compatibility with any Contact ID dialer – digital and Two-way Voice
- Delivery of all Contact ID signals to your central station to a dial-up or IP receiver
- Faster takeovers by entering the CS phone and account number in the dealer website to override panel programming

Mobile Apps

Alarm remote? We've got an app for that.



Uplink®Remote

- Customers gain remote access to control their alarm systems
- Designed to be dealer branded
- Easy-to-use customer portal & smartphone apps
- Flat rate monthly charge



Uplink®Installer

- Activate Uplink communicators quickly and easily from our mobile app
- Decrease overall install time
- Scan bar code to avoid possible errors
- Check signal strength at the push of a button

GPS Vehicle Tracking Services



Increased RMR by selling real-time GPS vehicle tracking

Supports multiple users and notification recipients

Click-to-locate, over-speed alerts, live tracking, trip reporting, geo-fence set-up, boundary violation alerts, and more.

UPLINKGPS™



- Ideal for family and small fleet tracking
- Simple installation in seconds
- Built-in antennas
- Self-contained unit with GPS receiver, GSM radio, and built-in antenna
- Plugs right into the vehicle – OBD port under the steering column
- Vehicle tracking system
- Tracks up to every 2 minutes

The advantage of

uplink®

Flat-rate billing

Fast and easy installation

Instant activation

Dial-up and internet receiver capable

**Test options:
monthly, weekly, daily**

Programmer not required

Optional Uplink Remote service