Effective November 2016 Supersedes June 2011

Manual pull stations



MPS-100 MPS-200



MPS-400X

Description

Wheelock MPS non-coded manual pull stations are constructed of high-quality, die-cast metal for long-lasting performance and may be mounted on a single gang backbox.

Available in either single or dual action configurations for indoor or outdoor use with SPST contacts and terminal strip connections. The normally open contact will close when the pull station is activated and is rated for 30 VDC @ 1 amp and/or 120 VAC @ 1 amp. The contacts are gold plated to avoid the risk of corrosion.

The single-action explosion-proof model MPS-400X is UL Listed and Factory Mutual approved for use in Class I, Division I, Groups B, C and D; Class II, Groups E, F and G; and Class III hazardous environments. It also has a marine rating and is approved for NEMA-4X applications. MPS Pull Stations are NEMA-3R listed when mounted to the MPS-WP weatherproof back box.

All models are painted red with raised white lettering and a locking mechanism to prevent unauthorized reset.



Features & benefits

- Approvals include: UL Standard, Factory Mutual (FM), California State Fire Marshal (CSFM) and New York City (MEA)
- Single or dual action
- Key reset
- Terminal strip connections
- Corrosion-resistant, gold-plated SPST contacts
- Mounts on single gang backbox
- · Surface and weatherproof backboxes available
- Plastic breakrod
- · High-gloss red enamel finish with raised white lettering

Note: Please read these specifications and associated installation instructions before using, specifying, or installing this product. Visit Eaton.com/massnotification for current installation instructions.

Table 1. Specifications and ordering information

station as far down as it will go, at which point the handle locks into place and is easily visible from up to 50 feet. The handle is reset by opening the station with a key, placing the handle in the normal upright position and relocking the station.

The Series MPS is operated by pulling the handle on the front of the

On dual action models (not shown), the push bar rotates inward allowing the Pull handle to be grasped in a one handed motion.

MPS-100 8400 Red SPST, single action, terminals, key reset MPS-200 ^① 8401 Red SPST, double action, terminals, key reset MPS-400X 8403 Red Explosion proof, single action, key reset	Mounting
	MPS-ISB, MPS-WP
MPS-400X 8403 Red Explosion proof, single action, key reset	MPS-ISB, MPS-WP
	Backbox provided
MPS-ISB 8404 Red Interior surface backbox	
MPS-WP 8405 Red Weatherproof backbox with gasket assembly	
MPS-RODS 8406 Red Scored acrylic breakrods (dozen)	

Operation:

① Consult Customer Service for availability.

Architects and engineers specifications

The non-coded manual pull stations shall be Wheelock MPS single action, double action or approved equals. They shall be constructed of a rugged die-cast metal housing with key reset and corrosion-resistant, gold-plated single or double pole, single or double throw contacts. The wiring connections shall be made via a terminal strip and the unit shall mount to a single gang backbox and when weatherproof manual pull stations are required, the backbox shall be the Wheelock MPS-WP backbox with gasket assembly. MPS pull stations shall be NEMA-3R listed when mounted to the MPS-WP weatherproof back box.

The MPS-400X shall be installed in installations that require explosion proof, Marine or NEMA 4X rated initiating devices. Temperature rating is -40°F to 150°F.

MPS-ISB dimensions shall be 4-3/4"H x 3-1/4" W x 2-1/4"D.

Note: Due to continuous development of our products, specifications and offerings are subject to change without notice in accordance with Cooper Wheelock, Inc., dba Eaton, standard terms and conditions.



WE ENCOURAGE AND SUPPORT NICET CERTIFICATION 3-YEAR WARRANTY

Eaton

1000 Eaton Boulevard Cleveland, OH 44122 United States Eaton.com

Eaton

Life safety & mass notification solutions 273 Branchport Ave. Long Branch, NJ 07740 www.eaton.com/massnotification

© 2016 Eaton All Rights Reserved Printed in USA Publication No. TD450082EN November 2016

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

