

2-599619-3

Fiber Optic Cable, 24-fiber, OM3, 2000 m, aqua

Body Features

Cable Color	Aqua
Cable Construction	2 x 12
Bend Radius (Installation)	229.87 mm 9.05 in
Bend Radius (Long Term)	169.93 mm 6.69 in
Tensile Strength (Installation)	2001.70 N 450.00 lbf
Tensile Strength (Long Term)	1201.02 N 270.00 lbf
Weight (Nominal)	119.0 kg/km

Configuration Features

Number of Fibers	24
Number of Fillers	2

Dimensions

Length	1999.99 m 6561.66 ft
Outside Diameter	11.50 mm 0.45 in

Industry Standards

Flammability Rating	ULSZH (Universal Low Smoke Zero Halogen)
---------------------	--

Operation/Application

Environment	Outdoor
-------------	---------

Product Availability

Region	Asia Australia/New Zealand EMEA
--------	-------------------------------------

Product Type Features

Product Type	Cable
Fiber Type	OM3
Armoring	None
Cable Type	Fiber Optic
Fiber Cable Buffering	Loose tube, dry
Fiber Diameter	50/125 μ m
Fiber Specification	IEC 60794-1
System	AMP NETCONNECT

Signal Characteristics

Attenuation, maximum (1300nm)	1.00 dB/km
Attenuation, maximum (850nm)	3.50 dB/km

Usage Conditions

2-599619-3

Installation Temperature Range -5 – 50 °C
Operating Temperature Range -10 – 70 °C | 14 – 158 °F
Storage Temperature Range -10 – 70 °C

Regulatory Compliance/Certifications

Agency
RoHS 2011/65/EU

Classification
Compliant