THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.



WITH PLUG CAPS

PANDUIT PART NUMBER	MIN. CABLE LENGTH	WEIGHT
IUTPCH3BLY	3 FT.	1.97 lbs/10 PCS (735.3 g/10 PCS
IUTPCH5BLY	5 FT.	2.53 lbs/10 PCS (944.3 g/10 PCS
IUTPCH7BLY	7 FT.	3.09 lbs/10 PCS (1153.3 g/10 PCS
IUTPCH10BLY	10 FT.	3.93 lbs/10 PCS (1784.2 g/10 PCS
IUTPCH15BLY	15 FT.	5.31 lbs/10 PCS (1981.9 g/10 PCS
IUTPCH20BLY	20 FT.	6.70 lbs/10 PCS (2500.7 g/10 PCS

NOTES:
- **1. SEE CURRENT CATALOG FOR VARIOUS APPLICATIONS AND TO INDICATE COLOR AND OR PACKAGE QUANTITY.
- 2. SEE CATALOG FOR A COMPLETE LIST OF PARTS APPLICABLE FOR USE WITH THIS PART.
- 3. DIMENSIONS IN [ ] ARE IN METRIC.
- 4. NUT ON STRAIN RELIEF TAIL MUST BE TORQUED TO 20 IN-LBS TO MAINTAIN IP67 RATING
- 5. CABLE MEETS CATEGORY 5E REQUIREMENTS AND CURRENT ODVA REQUIREMENTS FOR INDUSTRIAL CABLE.

WITHOUT PLUG CAPS

PANDUIT PART NUMBER	MIN. CABLE LENGTH	WEIGHT
IUTPCHNC3BLY	3 FT.	1.53 lbs/10 PCS (692.84 g/10 PCS
IUTPCHNC5BLY	5 FT.	1.99 lbs/10 PCS (901.84 g/10 PCS
IUTPCHNC7BLY	7 FT.	2.45 lbs/10 PCS (1110.84 g/10 PCS
IUTPCHNC10BLY	10 FT.	3.84 lbs/10 PCS (1741.74 g/10 PCS
IUTPCHNC15BLY	15 FT.	4.28 lbs/10 PCS (1939.41 g/10 PCS
IUTPCHNC20BLY	20 FT.	5.42 lbs/10 PCS (2458.24 g/10 PCS

T568A WIRING

PLUG POSITION	CABLE WIRE
1	WHITE GREEN
2	GREEN
3	WHITE ORANGE
4	BLUE
5	WHITE BLUE
6	ORANGE
7	WHITE BROWN
8	BROWN

REV	DATE	BY	CHK	APR	DESCRIPTION	ECN
1	6/13/14	JSP	REFR	MMR	A. REVISED DRAWING TITLE BLOCK.	02479-311
R	3-18-06	LZ	WJC	RMD	RELEASED TO PRODUCTION	02479-311

PART NUMBER
IUTPCH*BLY, IUTPCHNC*BLY

TITLE
CATEGORY 5E INDUSTRIALNET, UTP, SOLID, PATCH CORD WITH PANDUIT PLUGS

CUSTOMER DRAWING

ITEM REVISION NAME: M02479LX/00

DATASET FILE NAME: M02479LX_DC311/00B

UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN [mm]
.X ± .XXX ± .010 [.3]
.XX ± .03[.8] ANGLES ±
THIRD ANGLE PROJECTION

MATERIAL:

DRAWING NUMBER: 02479-311

DRAWN BY	DATE	CHK	SCALE	SHT 1 OF 1	SIZE
LZ	3-18-06	WJC	NONE		A

D10100DA/14