THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

PANDUIT P/N	WEIGHT
GM-A0259BL	6.33kg (14.01b)



REAR VIEW

NOTES:

1. IDENTIFICATION: VERTICAL, MIXED (24) C13 & (6) C19, GATEWAY-ENABLED MONITORED, 230/400V / 16A / THREE-PHASE WYE PDU

PART NO.	COLOR
GM-A0259BL	BLACK

2. ACCESSORY COMPONENTS:
   (1) QUICK-START GUIDE
3. PRIMARY DIMENSIONS ARE IN MILLIMETERS, SECONDARY DIMENSIONS IN [INCHES]
4. PHASE (L1, L2, L3) LEVEL POWER (AMPS, VOLTS, kWh, kVA, POWER FACTOR, FREQUENCY) MONITORING. WHEN CONNECTED VIA SERIAL CONNECTION TO GATEWAY, DATA CAN BE ACCESSED ON UNIT DISPLAY OR REMOTELY.
5. RoHS COMPLIANT.
6. VISIT OUR ON-LINE CATALOG AT WWW.PANDUIT.COM FOR A CURRENT LIST OF PRODUCTS APPLICABLE FOR USE WITH THIS PART.
7. MAXIMUM AVAILABLE INPUT POWER = 11.1 kW
8. INSTALLATION SHALL COMPLY WITH ALL APPLICABLE NATIONAL, STATE, AND LOCAL CODES.
9. PRINTED WITH CIRCUIT IDENTIFICATION



FRONT VIEW



SIDE VIEW



PLUG
16 AMP, 230/400V x 3-WYE
4P/5W
IEC 60309, SPLASHPROOF

TWENTY-FOUR (24)
RECEPTACLES
10 AMP, 250V
STRAIGHT BLADE
IEC 60320/C13

SIX (6)
RECEPTACLES
16 AMP, 250V
STRAIGHT BLADE
IEC 60320/C19

REV	DATE	BY	CHK	APR	DESCRIPTION	ECN
00A	10-23-14	GLM	GLM	EDM	RELEASED TO PRODUCTION	AA0259AP

WE ASK THAT YOU CHECK FULLY THE DIMENSIONS, NOTES, AND SIGN THE CLIENT SIGNATUTE BOX.

THE JOB WILL NOT PROGRESS WITHOUT SIGNED APPROVAL. PLEASE DO NOT DELAY IN RETURNING PROOF AS IT WILL AFFECT DELIVERY.

SIGN

DATE

PRINT

TITLE
SMARTZONE GATEWAY-ENABLED M SERIES RACK PDU
GM-A0259BL
CUSTOMER DRAWING

ITEM REVISION NAME
AA0259AP/00.PRT

DATASET FILE NAME
AA0259CP_DC/00A.PRT

UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE:

INCHES		METRIC - MILLIMETER		ANGLE
X.X	+/- 0.03	X.	+/- 0.8	+/- 1°
X.XX	+/- 0.018	X.X	+/- 0.46	
X.XXX	+/- 0.007	X.XX	+/- 0.18	

THIRD ANGLE PROJECTION

MATERIAL/COLOR:
N/A

DRAWING NUMBER:
AA0259AP_DC

DRAWN BY	DATE	CHK	SCALE	SHT 1 OF 1	SIZE
GLM	10-23-14	GLM	NONE		B