

1				
	PANDUIT P/N	WEI	GHT	
	GMSPO-A0290BL	X.XXkg	(XX.XIb)	
	VERTICAL, (18) C1 LOCKING, ONE (1) ON (BREAKER PROTE GATEWAY-ENABLED M MONITORED AND SWI 230V / 32A / SING	C13 LOCKIN CTED) ONITORED W TCHED PER	G ALWAYS ITH Outlet,	
90BL	<u>Color</u> Black			
5 IN [I	GUIDE NNS ARE IN MILLIME NCHES]	ŕ		B
) monit	?S, VOLTS, KWh, KV Oring. Data can b Ely when connecte Teway	E ACCESSED	on unit	
) MONIT NNECTIC	YER (AMPS, VOLTS, Toring can be acce on to gateway Ptacles can be swi	SSED REMOT	ELY VIA	
	IE CATALOG AT WWW. Products applicae			
ION SHA State,	E INPUT POWER = 7 LL COMPLY WITH AL AND LOCAL CODES SE & CIRCUIT IDEN	l applicab		
			63.6	
100T) — CORD	_/ 90.0 — - [3.54]		2.50]	
	<u>side view</u>			
DIMENSIONS, SIGNATUTE BO THE JOB WILL SIGNED APPRO IN RETURNING DELIVERY.	YOU CHECK FULLY THE SIGN NOTES, AND SIGN THE CLIENT X. DATE NOT PROGRESS WITHOUT VAL. PLEASE DO NOT DELAY PROOF AS IT WILL AFFECT PRIM	Ξ		A
SMARTZONE GATEWAY-ENABLED MSPO SERIES RACK PDU GMSPO-A0290BL customer drawing				
ATASET FILE NAM	ME 290CP_DC/01A.PRT			
JNLESS OTHERWIS	E SPECIFIED, DIMENSIONAL TOLERANCES AR	E: MATENIAE/COLOR:		
			I/A	

DRAWING NUMBER:

AA0290CP_DC

SHT 1 OF 1

В

THIRD ANGLE PROJECTION

NTS

SCALE

GLM

12/9/14

1