THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

PANDUIT P/N	WEIGHT
V1M2B1J0A30AHA0	7.0 kg (15.36 lbs)

NOTES:
1. IDENTIFICATION: VERTICAL, MIXED (24) C-13 & (6) C-19, METERED 208V / 20A / THREE-PHASE WYE PDU

PART NO.	COLOR
V1M2B1J0A30AHA0	BLACK

2. ACCESSORY COMPONENTS: (1) QUICK-START GUIDE
3. PRIMARY DIMENSIONS ARE IN MILLIMETERS, SECONDARY DIMENSIONS IN [INCHES].
4. POWER (e.g. AMPS, VOLTS, kWh, kVA, POWER FACTOR FREQUENCY) MONITORING DATA CAN BE ACCESSED VIA ON-UNIT DISPLAY.
5. RoHS COMPLIANT.
6. VISIT OUR ON-LINE CATALOG AT WWW.PANDUIT.COM FOR A CURRENT LIST OF PRODUCTS APPLICABLE FOR USE WITH THIS PART.
7. MAXIMUM AVAILABLE INPUT POWER = 5.7 kW
8. INSTALLATION SHALL COMPLY WITH ALL APPLICABLE NATIONAL, STATE, AND LOCAL CODES.
9. PRINTED WITH PHASE & CIRCUIT IDENTIFICATION.



FRONT VIEW



REAR VIEW



SIDE VIEW

PLUG
20 AMP, 250V x 3- WYE
TWIST LOCK
NEMA L21-20P

TWENTY-FOUR (24)
RECEPTACLES
15 AMP, 250V
STRAIGHT BLADE
IEC 60320/C13


SIX (6)
RECEPTACLES
20 AMP, 230V
STRAIGHT BLADE
IEC 60320/C19

REV	DATE	BY	CHK	APR	DESCRIPTION	ECN
02B	8/19/15	MRWA	RGO	EDM	C. ADDED CIRCUIT PHASE CALLOUTS B. CLEANED UP TOP VIEW A. DRAWING WAS LABELED "CONTROL"	12V091ZA
01A	09/11/14	PJST	MRWA	EDM	RELEASED TO PRODUCTION	12V091ZA

WE ASK THAT YOU CHECK FULLY THE DIMENSIONS, NOTES, AND SIGN THE CLIENT SIGNATUTE BOX.

THE JOB WILL NOT PROGRESS WITHOUT SIGNED APPROVAL. PLEASE DO NOT DELAY IN RETURNING PROOF AS IT WILL AFFECT DELIVERY.

SIGN

DATE

PRINT

TITLE

BASIC WITH LOCAL METER PDU (24) C13 & (6) C19

CUSTOMER DRAWING

ITEM REVISION NAME: 12V091ZA/01.PRT

DATASET FILE NAME: 12V091ZA_DC/01B.PRT

UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE:

INCHES		METRIC - MILLIMETER		ANGLE
X.X	+/- 0.03	X.	+/- 0.8	+/- 1°
X.XX	+/- 0.018	X.X	+/- 0.46	
X.XXX	+/- 0.007	X.XX	+/- 0.18	

THIRD ANGLE PROJECTION

MATERIAL/COLOR: N/A

DRAWING NUMBER: 12V091ZA-DC

DRAWN BY	DATE	CHK	SCALE	SIZE
PJST	09/11/14	MRWA	NONE	B

SHT 1 OF 1