

PRODUCT DATA SHEET

Perma-Mend™ UV Curable Repair Patch No. 14096

Product Description Light activated fiberglass reinforced self adhesive repair

patch.

Applications Repair of tanks, pipes, roofs, steps, switch boxes,

radiators, mufflers, bumpers, boat bodies. Can be used on any wood, metal, glass, ceramic, concrete and plastic

surface.

Unit Package Description 9" x 12" Patch

Brand CRC

Generic Description 1 Repair Patch

Net Fill 9" x 12"

UPC Code 078254140964

Unit Dimensions 9H x 12W

Units Per Case 12

Case Dimensions 2.25H x 11.5W x 15.75D in

Cases Per Pallet 50

Case Weight 10 lbs

I 2 of 5 Code 30078254140965

Appearance Grey Sheet Lamination

Flash point (F) 840°F
Flash point (C) 449°C
Flammability Class - CPSC None

Plastic Safe Yes

Curing Time 5 Minutes (Sunny),50 Minutes (Cloudy)

Dielectric Strength 9 kV/mm

Working Temp (F) -40 to 392°F
Working Temp (C) -40 to 200°C
DOT Proper Shipping Name Not Regulated

VOC % (Federal) 0.6

VOC g/L (Federal) Not Determined

Last revised: 6/17/2016

Page 1 of 2



ISO 9001:2008 CRC*, K&W*, Sta



PRODUCT DATA SHEET



VOC Lbs./Gal. (Federal)
VOC Category

Not Determined Not Regulated

Last revised: 6/17/2016

Page 2 of 2



of CRC Industries, Inc.