

PRODUCT DATA SHEET



Permatherm[™] High Temp Synthetic Grease, 35 Lbs No. SL3585

Product Description

Applications

Unit Package Description Brand **Generic Description 1** Net Fill UPC Code Unit Dimensions Units Per Case **Case Dimensions** Cases Per Pallet Case Weight Appearance Base Type Flash point (F) Flash point (C) Flammability Class - CPSC Spec Gravity Concentrate NLGI Grade Timken OK Load Lbs. Plastic Safe **Evaporation Rate** Working Temp (F) Working Temp (C)

A high performance synthetic grease that incorporates a non-melting thickener. Its proprietary chemistry provides exceptional anti-wear properties up to 600 F.

Clinker cooler bearings, fans, high temperature applications, high temperature pumps, mining applications, ovens, overhead oven trolleys, paper machine dryers, pumps, super heated steam dryers, treadmills

35 Pound Pail Sta-Lube High Temp Synthetic Grease 35 Lb 072213358506 14.5H x 12W x 12D in 1 14.5H x 12W x 12D in 36 40 lbs Amber Semi-Solid to Solid Grease Fumed Silica 500°F 260°C None 0.9 at 60°F 1.5 50 Lbs Not Determined <1 (butyl acetate=1) -40 to 400°F -40 to 204°C

> Last revised: 12/28/2016 Page 1 of 2



Customer Care: 800-556-5074 Technical Assistance: 800-521-3168 www.crcindustries.com



CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.

> CRC[®], K&W[®], Sta-Lube[®], Marykate[®] and products denoted with [®] and [™] are trademarks of CRC Industries, Inc.




PRODUCT DATA SHEET



4 Ball EP	Not Determined
4 Ball Wear	0.5 mm
Drop Point	600°F
Leakage	Not Determined
Oil Separation	1%
Oxidation Stability	5
Pour Point (F)	Not Determined
Pour Point (C)	Not Determined
ISO Viscosity Grade	450
Water Washout	<5
Worked Penetration	275 to 305
Propellant	None
DOT Proper Shipping Name	Not Regulated
VOC % (Federal)	<0.1
VOC g/L (Federal)	<0.9
VOC Lbs./Gal. (Federal)	<0.007
VOC Category	Not Regulated
Removal (How To)	Remove with a degreaser or brake cleaner product.



Customer Care: 800-556-5074 Technical Assistance: 800-521-3168 www.crcindustries.com



CRC*, K&W*, Sta-Lube*, Marykate* and products denoted with * and ™ are trademarks of CRC Industries, Inc.

Last revised: 12/28/2016 Page 2 of 2