



## PRODUCT DATA SHEET

Super White™ Multi-Purpose Lithium Grease, 10 Wt Oz  
No. SL3360

### Product Description

A high purity, NLGI Grade 2 multi-purpose white lithium grease. Provides superior lubrication & durability in any weather and most temperatures. Bright white in color. Ideal for when appearance is important.

### Applications

Assembly lubes, bearings, break-in lubrication for bearings, cables, chains, chassis points, conveyor bearings, door tracks, garage door channels & openers, hinges, latches, machinery, open gears, overhead door tracks, roller bearings, sleeve bearings.

### Unit Package Description

10 Ounce Tube

### Brand

Sta-Lube

### Generic Description 1

Super White Multi-Purpose Grease

### Net Fill

10 Wt Oz

### UPC Code

072213336009

### Unit Dimensions

10H x 3W x 2D in

### Units Per Case

6

### Case Dimensions

4.13H x 6.75W x 10.25D in

### Cases Per Pallet

250

### Case Weight

5 lbs

### I 2 of 5 Code

30072213336000

### Appearance

White Semi-Solid to Solid Grease

### Base Type

Lithium-12

### Flash point (F)

475°F

### Flash point (C)

246°C

### Flammability Class - CPSC

None

### Spec Gravity Concentrate

0.9 at 60°F

### NLGI Grade

2

### Timken OK Load Lbs.

25 Lbs

### Plastic Safe

Not Determined

### Evaporation Rate

<0.01 (Butyl Acetate=1)



Last revised: 5/4/2016  
Page 1 of 2



Customer Care: 800-556-5074  
Technical Assistance: 800-521-3168  
www.crcindustries.com

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.



## PRODUCT DATA SHEET



Working Temp (F)	0 to 300°F
Working Temp (C)	-17.8 to 148.9°C
Drop Point	350°F
Leakage	5
Oil Separation	5
Oxidation Stability	10
Pour Point (F)	0°F
Pour Point (C)	-17.78°C
ISO Viscosity Grade	165
Water Washout	10
Worked Penetration	285 to 295
Propellant	None
NSF Category Code	H2
NSF Number	147593
DOT Proper Shipping Name	Not Regulated
VOC % (Federal)	<0.1
VOC g/L (Federal)	<0.9
VOC Lbs./Gal. (Federal)	<0.01
VOC Category	Not Regulated
Removal (How To)	Remove with a degreaser or brake cleaner product.

Last revised: 5/4/2016  
Page 2 of 2



Customer Care: 800-556-5074  
Technical Assistance: 800-521-3168  
[www.crcindustries.com](http://www.crcindustries.com)

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.